SAFETY DATA SHEET

1. Identification

Product identifier LPS® HDX (Aerosol)

Other means of identification

Part Number 01020

Recommended use A degreaser designed to remove grease, oil, dirt and other residues from metal and other hard

surfaces near ignition sources.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Manufacturer

Company name LPS Laboratories, a division of Illinois Tool Works, Inc.

Address 4647 Hugh Howell Rd.

Tucker, GA 30084

Country (U.S.A.)

Tel: +1 770-243-8800

In Case of Emergency 1-800-424-9300 (inside U.S.)

+001 703-527-3887 (outside U.S.)

Website www.lpslabs.com E-mail sds@lpslabs.com

2. Hazard(s) identification

Physical hazards Gases under pressure Compressed gas

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2A
Germ cell mutagenicity Category 2
Carcinogenicity Category 1B

Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Contains gas under pressure; may explode if heated. Causes skin irritation. Causes serious eye

irritation. Suspected of causing genetic defects. May cause cancer. May cause drowsiness or

dizziness.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Avoid breathing mist or vapor. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If on skin: Wash with plenty of water. If skin irritation occurs: Get medical advice/attention.

Specific treatment (see this label). Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel

unwell. If exposed or concerned: Get medical advice/attention.

Storage Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Store locked

up.

Material name: LPS® HDX (Aerosol) 784 Version #: 01 Issue date: 06-18-2014 **Disposal**

Hazard(s) not otherwise

Dispose of contents/container in accordance with local/regional/national/international regulations.

classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
1,1,2-trichloroethylene		79-01-6	90 - 100
Carbon Dioxide		124-38-9	1 - 5

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. For breathing

difficulties, oxygen may be necessary. Call a physician if symptoms develop or persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eve contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Call a physician or poison control center immediately. Only induce vomiting at the instruction of medical personnel. Never give anything by mouth to an unconscious person. If vomiting occurs,

keep head low so that stomach content doesn't get into the lungs.

Most important

symptoms/effects, acute and

delayed

Dermatitis. Rash. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Skin irritation. May cause redness and pain.

Indication of immediate medical attention and special

treatment needed

Provide general supportive measures and treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Call a POISON CENTER or doctor/physician if you feel unwell.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

General information

media

Dry chemical powder. Carbon dioxide (CO2). Water spray, fog or regular foam.

None known.

Specific hazards arising from

the chemical

Contents under pressure. Pressurized container may explode when exposed to heat or flame.

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

In case of fire: Stop leak if safe to do so. Do not move cargo or vehicle if cargo has been exposed to heat. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Cool containers exposed to flames with water until well after the fire is out. Specific methods

General fire hazards No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protective equipment. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. Use personal protection recommended in Section 8 of the SDS.

Methods and materials for containment and cleaning up Refer to attached safety data sheets and/or instructions for use. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

Material name: LPS® HDX (Aerosol)

784 Version #: 01 Issue date: 06-18-2014

SDS US

7. Handling and storage

Precautions for safe handling Pressu

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial

well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Contents under pressure. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store locked up. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

Components	Туре	, Value	Form	
Butanone (CAS 78-93-3)	PEL	590 mg/m3		
		200 ppm		
Camphor USP (CAS 76-22-2)	PEL	2 mg/m3		
Carbon Dioxide (CAS	PEL	9000 mg/m3		
124-38-9)		5000 ppm		
Dial- and Orida (OAO	DEL	• •	V/=	
Diphenyl Oxide (CAS 101-84-8)	PEL	7 mg/m3	Vapor.	
		1 ppm	Vapor.	
lso amyl acetate (CAS 123-92-2)	PEL	525 mg/m3		
,		100 ppm		
Turpentine (CAS 8006-64-2)	PEL	560 mg/m3		
,		100 ppm		
US. OSHA Table Z-2 (29 CFR 1910	.1000)			
Components	Туре	Value		
1,1,2-trichloroethylene (CAS 79-01-6)	Ceiling	200 ppm		
(/	TWA	100 ppm		
US. ACGIH Threshold Limit Values	S			
Components	Туре	Value	Form	
		25 ppm		
	STEL			
1,1,2-trichloroethylene (CAS 79-01-6)				
(CAS 79-01-6)	TWA	10 ppm		
(CAS 79-01-6)	TWA STEL	10 ppm 300 ppm		
(CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS	TWA	10 ppm		
(CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS	TWA STEL TWA STEL	10 ppm 300 ppm 200 ppm 3 ppm		
(CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2)	TWA STEL TWA STEL	10 ppm 300 ppm 200 ppm 3 ppm 2 ppm		
(CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS	TWA STEL TWA STEL TWA STEL	10 ppm 300 ppm 200 ppm 3 ppm 2 ppm 30000 ppm		
(CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS 124-38-9)	TWA STEL TWA STEL TWA STEL TWA	10 ppm 300 ppm 200 ppm 3 ppm 2 ppm 30000 ppm		
(CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS 124-38-9) Diphenyl Oxide (CAS	TWA STEL TWA STEL TWA STEL	10 ppm 300 ppm 200 ppm 3 ppm 2 ppm 30000 ppm	Vapor.	
(CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS 124-38-9) Diphenyl Oxide (CAS	TWA STEL TWA STEL TWA STEL TWA	10 ppm 300 ppm 200 ppm 3 ppm 2 ppm 30000 ppm	Vapor. Vapor.	
(CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS 124-38-9) Diphenyl Oxide (CAS 101-84-8) Iso amyl acetate (CAS	TWA STEL TWA STEL TWA STEL TWA STEL	10 ppm 300 ppm 200 ppm 3 ppm 2 ppm 30000 ppm 5000 ppm 2 ppm	•	
(CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS 124-38-9) Diphenyl Oxide (CAS 101-84-8) Iso amyl acetate (CAS	TWA STEL TWA STEL TWA STEL TWA STEL TWA STEL	10 ppm 300 ppm 200 ppm 3 ppm 2 ppm 30000 ppm 5000 ppm 2 ppm 1 ppm 100 ppm	•	
1,1,2-trichloroethylene (CAS 79-01-6) Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS 124-38-9) Diphenyl Oxide (CAS 101-84-8) Iso amyl acetate (CAS 123-92-2) Turpentine (CAS 8006-64-2)	TWA STEL TWA STEL TWA STEL TWA STEL TWA STEL	10 ppm 300 ppm 200 ppm 3 ppm 2 ppm 30000 ppm 5000 ppm 2 ppm	•	

Material name: LPS® HDX (Aerosol)

SDS US

784 Version #: 01 Issue date: 06-18-2014

Components	Туре	Value	Form
1,1,2-trichloroethylene (CAS 79-01-6)	TWA	25 ppm	
Butanone (CAS 78-93-3)	STEL	885 mg/m3 300 ppm	
	TWA	590 mg/m3	
	IWA	200 ppm	
Camphor USP (CAS 76-22-2)	TWA	2 mg/m3	
Carbon Dioxide (CAS 124-38-9)	STEL	54000 mg/m3	
·		30000 ppm	
	TWA	9000 mg/m3	
		5000 ppm	
Diphenyl Oxide (CAS 101-84-8)	TWA	7 mg/m3	Vapor.
		1 ppm	Vapor.
lso amyl acetate (CAS 123-92-2)	TWA	525 mg/m3	
,		100 ppm	
Turpentine (CAS 8006-64-2)	TWA	560 mg/m3	
0000 01 2)		100 ppm	
US. Workplace Environmental Ex	posure Level (WEEL) Guides		
Components	Туре	Value	
1,2 Butylene Oxide (CAS 106-88-7)	TWA	5.9 mg/m3	
,		2 ppm	

Biological limit values

Components	Value	Determinant	Specimen	Sampling Time
1,1,2-trichloroethylene (CAS 79-01-6)	15 mg/l	Trichloroacetic acid	Urine	*
	0.5 mg/l	Trichloroethano I, without hydrolysis	Blood	*
Butanone (CAS 78-93-3)	2 mg/l	MEK	Urine	*

^{* -} For sampling details, please see the source document.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Eye wash fountain is recommended.

Skin protection

Hand protection Chemical resistant gloves are recommended.

Other Avoid contact with the skin. Wear appropriate chemical resistant clothing.

Respiratory protection When workers are facing concentrations above the exposure limit they must use appropriate

certified respirators.

Thermal hazards Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance Clear. Liquid.

Physical state Gas.

Form Aerosol.

Color Clear, Colorless
Odor Sweet, Spice
Odor threshold Not established
pH Not applicable
Melting point/freezing point Not established

Initial boiling point and boiling

188.6 ℉ (87 ℃)

range

Flash point Tag Closed Cup (None)
Evaporation rate 0.3 (Ethyl Ether = 1)
Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

8 %

(%)

Flammability limit - upper

10.5 %

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 58 mm Hg @ 20 ℃

Vapor density 4.5

Relative density Not available.

Solubility(ies)

Solubility (water) 0.1 % Partition coefficient 2.4

(n-octanol/water)

Auto-ignition temperature $> 788 \,^{\circ}\text{F} \ (> 420 \,^{\circ}\text{C})$ Decomposition temperatureNot establishedViscosity $0.53 \,^{\circ}\text{C} \,^{\circ}\text{C}$

Other information

Explosive properties Not established.

Heat of combustion < 20 kJ/g

Oxidizing properties Not established.

Percent volatile 100 %

Specific gravity 1.41 - 1.47 @ 20 ℃

VOC (Weight %) 97.8 %

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions.

Possibility of hazardous

Hazardous polymerization does not occur.

reactions

Conditions to avoid Keep away from heat, sparks and open flame. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents. Reacts violently with sodium, potassium, barium metal. Reacts with finely

divided aluminum, zinc and magnesium.

Hazardous decomposition

products

Irritating and/or toxic fumes and gases may be emitted upon the products decomposition.

Hydrogen chloride. Chlorine. Phosgene.

11. Toxicological information

Information on likely routes of exposure

Ingestion May cause discomfort if swallowed.

Inhalation Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Skin contact Causes skin irritation.

Eye contact Causes serious eye irritation.

Symptoms related to the physical, chemical and toxicological characteristics

Irritating to eyes, respiratory system and skin. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Exposure may cause temporary irritation, redness, or discomfort. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea.

Information on toxicological effects

Acute toxicity	Narcotic effects.	

Components	Species	Test Results
1,1,2-trichloroethylene (CAS 7	9-01-6)	
Acute		
Dermal		
LD50	Rabbit	20 ml/kg
Inhalation		
LC50	Mouse	8450 mg/l, 4 Hours
	Rat	26000 mg/l, 1 Hours
		12000 mg/l, 4 Hours
LD50	Mouse	49000 mg/l, 30 Minutes
		5500 mg/l, 10 Hours
NOEL	Ape	730 mg/l
	Guinea pig	730 mg/l
	Rabbit	1200 mg/l, 473 Hours
		730 mg/l
	Rat	100 mg/l, 8 Hours
Oral		
LD50	Dog	5680 mg/kg
	Mouse	2402 mg/kg
	Rat	4920 mg/kg
Other		
LD100	Mouse	5500 mg/kg
LD50	Dog	2783 mg/kg
	Mouse	2402 mg/kg
	Rabbit	29 g/kg
1,2 Butylene Oxide (CAS 106-	88-7)	
Acute		
Dermal		
LD50	Rabbit	2100 mg/kg
Inhalation		
LC100	Rat	8000 mg/l, 4 Hours
Oral	Б.,	500 #
LD50	Rat	500 mg/kg
Butanone (CAS 78-93-3)		
Acute Dermal		
LD50	Rabbit	> 8000 mg/kg
LDOU	Habbit	> 10 ml/kg
Inhalation		> 10 m/kg
LC50	Mouse	11000 mg/l, 45 Minutes
	Rat	11700 mg/l, 4 Hours
Oral	···	11700 mg/1, + 110010
LD50	Mouse	670 mg/kg
	Rat	2054 mg/kg
		· · ···ʊ

Material name: LPS® HDX (Aerosol)

SDS US

784 Version #: 01 Issue date: 06-18-2014

Components	Species	Test Results
		4.29 ml/kg
Other		
LD50	Mouse	1660 g/kg, 24 Hours
	Rat	12290 mg/kg, 24 Hours
Camphor USP (CAS 76-22-2)		
Acute		
Oral		
LD50	Mouse	1310 mg/kg
Other		
LD50	Mouse	3000 mg/kg
	Rat	70 mg/kg
Diphenyl Oxide (CAS 101-84-8)		
Acute		
Dermal		
LD50	Rabbit	> 7940 mg/kg
Oral		
LD100	Guinea pig	4 g/kg
	Rat	4 g/kg
LD50	Rat	2.83 g/kg
Iso amyl acetate (CAS 123-92-2)	
Acute		
Dermal		
LD50	Rabbit	> 5 g/kg
Oral		
LD50	Rabbit	7400 mg/kg
	Rat	16600 mg/kg
Turpentine (CAS 8006-64-2)		
Acute		
Dermal		
LD50	Rabbit	> 2000 mg/kg
Inhalation		
LC50	Mouse	29 mg/l
		29 mg/l, 2 Hours
	Rat	3590 mg/l, 1 Hours
		12 mg/l, 6 Hours
Oral		
LD50	Rat	3700 mg/kg
		4.6 ml/kg
Other		
LD50	Mouse	1180 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye	Causes serious eye irritation.	
irritation		
Respiratory or skin sensitization	on	
ACGIH sensitization		
Turpentine (CAS 8006-	64-2) Sensitiser.	
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	This product is not expected to cause skin	sensitization.
Germ cell mutagenicity	Suspected of causing genetic defects.	

Carcinogenicity May cause cancer.

ACGIH Carcinogens

1,1,2-trichloroethylene (CAS 79-01-6)

A2 Suspected human carcinogen. Camphor USP (CAS 76-22-2) A4 Not classifiable as a human carcinogen. Turpentine (CAS 8006-64-2) A4 Not classifiable as a human carcinogen.

IARC Monographs. Overall Evaluation of Carcinogenicity

1,1,2-trichloroethylene (CAS 79-01-6) 1 Carcinogenic to humans.

2B Possibly carcinogenic to humans. 1,2 Butylene Oxide (CAS 106-88-7)

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

1,1,2-trichloroethylene (CAS 79-01-6) Reasonably Anticipated to be a Human Carcinogen.

Based on available data, the classification criteria are not met. Reproductive toxicity

Specific target organ toxicity -

single exposure

Narcotic effects.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
1,1,2-trichloroethylene	e (CAS 79-01-6)		
Aquatic			
Fish	LC50	Flagfish (Jordanella floridae)	3.1 mg/l, 96 hours
Butanone (CAS 78-93	3-3)		
Aquatic			
Crustacea	EC50	Water flea (Daphnia magna)	4025 - 6440 mg/l, 48 hours
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	> 400 mg/l, 96 hours
Diphenyl Oxide (CAS	101-84-8)		
Aquatic			
Fish	LC50	Sheepshead minnow (Cyprinodon variegatus)	1.8 - 3.2 mg/l, 96 hours

Persistence and degradability Not inherently biodegradable.

Bioaccumulative potential Not available.

Partition coefficient n-octanol / water (log Kow)

LPS® HDX (Aerosol) 2.4 1,1,2-trichloroethylene 2.61 Butanone 0.29 Diphenyl Oxide 4.21

Mobility in soil No data available. Other adverse effects None known.

13. Disposal considerations

Disposal instructions Consult authorities before disposal. Contents under pressure. Do not puncture, incinerate or crush.

This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical

or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Dispose in accordance with all applicable regulations. Local disposal regulations

Hazardous waste code D003: Waste Reactive material

D040: Waste Trichloroethylene

Material name: LPS® HDX (Aerosol) 784 Version #: 01 Issue date: 06-18-2014 Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied. Do not re-use empty containers.

14. Transport information

DOT

UN1950 **UN number**

UN proper shipping name Aerosols, non-flammable, (each not exceeding 1 L capacity)

Transport hazard class(es)

Class 2.2 Subsidiary risk 6.1(PGIII) Label(s) 2.2

Packing group Not applicable.

Environmental hazards

Marine pollutant No

Special precautions for user Not available.

Packaging exceptions 306 Packaging non bulk None None Packaging bulk

IATA

UN number UN1950

UN proper shipping name Aerosols, non-flammable

Transport hazard class(es)

Class 2.2 6.1(PGIII) Subsidiary risk **Packing group** Not applicable.

Environmental hazards No **ERG Code** 2L

Special precautions for user Not available.

Other information

Passenger and cargo

Allowed.

aircraft

Allowed. Cargo aircraft only

IMDG

UN number UN1950 **UN** proper shipping name **AEROSOLS**

Transport hazard class(es)

2.2 Class Subsidiary risk 6.1(PGIII) Not applicable. Packing group

Environmental hazards

Marine pollutant No F-D, S-U **EmS** Special precautions for user Not available.

Transport in bulk according to This substance/mixture is not intended to be transported in bulk. Annex II of MARPOL 73/78 and

the IBC Code

DOT



IATA; IMDG



15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

1,1,2-trichloroethylene (CAS 79-01-6)Listed.1,2 Butylene Oxide (CAS 106-88-7)Listed.Butanone (CAS 78-93-3)Listed.Iso amyl acetate (CAS 123-92-2)Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - Yes Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

1,1,2-trichloroethylene (CAS 79-01-6) 1,2 Butylene Oxide (CAS 106-88-7)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act Not regulated.

(SDWA)

Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2) and Chemical Code Number

Butanone (CAS 78-93-3) 6714

Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Butanone (CAS 78-93-3) 35 % weight/volumn

DEA Exempt Chemical Mixtures Code Number

Butanone (CAS 78-93-3) 6714

US state regulations

US. Massachusetts RTK - Substance List

1,1,2-trichloroethylene (CAS 79-01-6)

1,2 Butylene Oxide (CAS 106-88-7)

Butanone (CAS 78-93-3)

Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS 124-38-9) Diphenyl Oxide (CAS 101-84-8) Iso amyl acetate (CAS 123-92-2) Turpentine (CAS 8006-64-2)

US. New Jersey Worker and Community Right-to-Know Act

1,1,2-trichloroethylene (CAS 79-01-6) 1,2 Butylene Oxide (CAS 106-88-7)

Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS 124-38-9) Diphenyl Oxide (CAS 101-84-8) Iso amyl acetate (CAS 123-92-2) Turpentine (CAS 8006-64-2)

US. Pennsylvania Worker and Community Right-to-Know Law

1,1,2-trichloroethylene (CAS 79-01-6) 1,2 Butylene Oxide (CAS 106-88-7)

Butanone (CAS 78-93-3) Camphor USP (CAS 76-22-2) Carbon Dioxide (CAS 124-38-9) Diphenyl Oxide (CAS 101-84-8) Iso amyl acetate (CAS 123-92-2)

US. Rhode Island RTK

1,1,2-trichloroethylene (CAS 79-01-6) 1,2 Butylene Oxide (CAS 106-88-7) Butanone (CAS 78-93-3)

Iso amyl acetate (CAS 123-92-2)

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

1,1,2-trichloroethylene (CAS 79-01-6) Listed: April 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory *A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

06-18-2014 Issue date

Version # 01

Disclaimer Not available.

Material name: LPS® HDX (Aerosol)

Yes