

# **SAFETY DATA SHEET**

## Section 1. Identification

Manufactured for: Kimball Midwest

4800 Roberts Road Columbus, OH 43228 Tel: (800) 233-1294

**Emergency telephone** 

number

(800) 424-9300 (24 Hours) Chemtrec

Product name Quickcrete Hand Kneadable Epoxy Putty

Code 80-202

Specific uses Sealants and adhesives

## Section 2. Hazards identification

OSHA/HCS status This material is considered hazardous by the OSHA Hazard Communication Standard

(29 CFR 1910.1200).

Classification of the SKIN CORROSION/IRRITATION - Category 2

substance or mixture SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 2B

SKIN SENSITIZATION - Category 1

**GHS label elements** 

**Hazard pictograms** 



Signal word Warning!

**Hazard statements** Causes skin and eye irritation.

May cause an allergic skin reaction.

**Precautionary statements** 

Prevention Wear protective gloves. Wear eye or face protection. Avoid breathing dust. Wash

hands thoroughly after handling. Contaminated work clothing should not be allowed out

of the workplace.

Response IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing.

Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical attention. IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get

medical attention.

Storage Not applicable.

Disposal Dispose of contents and container in accordance with all local, regional, national and

international regulations.

Hazards not otherwise

classified

None known.

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 1/11

# Section 3. Composition/information on ingredients

Substance/mixture

Mixture

Ingredient name	% by weight	CAS number
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin crystalline silica non-respirable	10 - 30 0.1 - 1	25068-38-6 14808-60-7

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First aid measures

#### **Description of necessary first aid measures**

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not

breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial

respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar,

tie, belt or waistband.

**Skin contact** Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash

contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly

before reuse.

**Eye contact** Immediately flush eyes with plenty of water, occasionally lifting the upper and lower

eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10

minutes. Get medical attention.

**Ingestion** Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and

keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain

an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

**Inhalation** No known significant effects or critical hazards.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Eye contact** Causes serious eye irritation.

**Ingestion** Irritating to mouth, throat and stomach.

### **Over-exposure signs/symptoms**

Inhalation No specific data.

**Skin contact** Adverse symptoms may include the following:

irritation redness

**Eye contact** Adverse symptoms may include the following:

pain or irritation

watering redness

**Ingestion** No specific data.

## Indication of immediate medical attention and special treatment needed, if necessary

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 2/11

INSTACRETE 7 INCH EPOXY STICK

## Section 4. First aid measures

Notes to physician Treat symptomatically. Contact poison treatment specialist immediately if large quantities

have been ingested or inhaled.

**Specific treatments** No specific treatment.

See toxicological information (Section 11)

## Section 5. Fire-fighting measures

### **Extinguishing media**

Suitable extinguishing

media

**Unsuitable extinguishing** 

media

Use an extinguishing agent suitable for the surrounding fire.

None known.

Specific hazards arising from the chemical

No specific fire or explosion hazard.

**National Fire Protection Association (U.S.A.)** 

Health 2 0

**Flammability** 

Instability/Reactivity

**Special** 

Hazardous thermal decomposition products

Decomposition products may include the following materials:

carbon dioxide carbon monoxide sulfur oxides

halogenated compounds metal oxide/oxides

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate

personal protective equipment.

For emergency responders

If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

## Methods and materials for containment and cleaning up

**Small spill** 

Move containers from spill area. Avoid dust generation. Using a vacuum with HEPA filter will reduce dust dispersal. Place spilled material in a designated, labeled waste container. Dispose of via a licensed waste disposal contractor.

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 3/11

## Section 6. Accidental release measures

### Large spill

Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Avoid dust generation. Do not dry sweep. Vacuum dust with equipment fitted with a HEPA filter and place in a closed, labeled waste container. Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

# Section 7. Handling and storage

Conditions for safe storage, including any incompatibilities

Store between the following temperatures: 5 to 30°C (41 to 86°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## **Precautions for safe handling**

**Protective measures** 

Put on appropriate personal protective equipment (see Section 8). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

Advice on general occupational hygiene

Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

## Section 8. Exposure controls/personal protection

### **Control parameters**

### Occupational exposure limits

Ingredient name	CAS#	Exposure limits
crystalline silica non-respirable	14808-60-7	OSHA PEL Z3 (United States, 9/2005). Notes: 250/(%SiO2+5) TWA: 250 MPPCF / (%SiO2+5) 8 hours. Form: Respirable OSHA PEL Z3 (United States, 9/2005). Notes: 10/(SiO2+2) TWA: 10 MG/M3 / (%SiO2+2) 8 hours. Form: Respirable ACGIH TLV (United States, 3/2012). TWA: 0.025 mg/m³ 8 hours. Form: Respirable fraction NIOSH REL (United States, 1/2013). TWA: 0.05 mg/m³ 10 hours. Form: respirable dust OSHA PEL Z3 (United States, 9/2005). Notes: 30/(%SiO2+2) TWA: 30 MG/M3 / (%SiO2+2) 8 hours. Form: Total dust.

Appropriate engineering

**Environmental exposure controls** 

Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## **Individual protection measures**

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 4/11

# Section 8. Exposure controls/personal protection

Hygiene measures Wash hands, forearms and face thoroughly after handling chemical products, before

eating, smoking and using the lavatory and at the end of the working period.

Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety

showers are close to the workstation location.

Respiratory protection Use a properly fitted, particulate filter respirator complying with an approved standard if

a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working

limits of the selected respirator.

Skin protection

Hand protection Chemical-resistant, impervious gloves complying with an approved standard should be

worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the

protection time of the gloves cannot be accurately estimated.

**Body protection** Personal protective equipment for the body should be selected based on the task being

performed and the risks involved and should be approved by a specialist before

handling this product.

Other skin protection Appropriate footwear and any additional skin protection measures should be selected

based on the task being performed and the risks involved and should be approved by a

specialist before handling this product.

Eye/face protection Safety eyewear complying with an approved standard should be used when a risk

assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles.

## Section 9. Physical and chemical properties

Physical state Solid.

Color White.-Gray. [Light]

Odor Pungent.-Sulfurous. [Strong]

Odor threshold

pH

Not available.

Melting point

Not available.

Boiling point

Not available.

Flash point Closed cup: >93.3°C (>199.9°F) [Setaflash.] [Product does not sustain combustion.]

Evaporation rate Not applicable.
Flammability (solid, gas) Not available.
Lower and upper explosive Not available.

(flammable) limits

Vapor pressureNot available.Vapor densityNot available.

Relative density 2.03

**Solubility** Easily soluble in the following materials: methanol and acetone.

Insoluble in the following materials: cold water and hot water.

Solubility in water Not applicable.

Auto-ignition temperature Not available.

Decomposition temperature >220°C (>428°F)

Viscosity Kinematic (40°C (104°F)): Not applicable.

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 5/11

# Section 10. Stability and reactivity

**Reactivity**No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** The product is stable.

Possibility of hazardous

reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Conditions to avoid No specific data.

**Incompatible materials** No specific data.

**Hazardous decomposition** 

products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

# Section 11. Toxicological information

## Information on toxicological effects

## **Acute toxicity**

No specific data.

#### **Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin	Eyes - Mild irritant	Rabbit	-	100 milligrams	-
	Skin - Moderate irritant	Rabbit	-	24 hours 500 microliters	-
	Skin - Severe irritant	Rabbit	-	24 hours 2 milligrams	-

### **Sensitization**

No specific data.

#### **Mutagenicity**

No specific data.

#### Carcinogenicity

No specific data.

#### Conclusion/Summary

: IARC classifies TiO2 as a 2B carcinogen based in large part on several studies of the effects of the inhalation of TiO2 on animals in which the TiO2 particles were of various sizes. Particles defined as "ultrafine" have been shown to cause cancer in animals exposed to very high concentrations. A number of authorities have reviewed those studies and others involving exposure to ultrafine particles and have concluded that the effects result from overloading the respiratory system of the animals. The effects observed, according to the scientists, are not due to TiO2 but are general responses to high levels of dust in the lungs. In addition, a carcinogenic effect of TiO2 dust in the workers was not observed in several epidemiology studies on more than 20,000 TiO2 industry workers in Europe and the USA, nor were other chronic diseases, including other respiratory diseases, associated with exposure to TiO2 dust. Accordingly, we have concluded that our products should not be classified on the basis of the presence of TiO2 in the products.

This product contains talc in a polymer matrix. Sanding the cured product may release particles containing talc with the polymer and Vother components of the matrix into the air. The talc contains less than 1% crystalline silica. Appropriate evaluations of the use of the product should be performed to determine if exposure to talc occurs due to handling and use. If such exposures occur, appropriate precautions must be taken to

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 6/11

# **Section 11. Toxicological information**

prevent exposure in excess of the OSHA Permissible Exposure Limit (PEL).

### **Classification**

Product/ingredient name	OSHA	IARC	NTP
crystalline silica non- respirable	-	1	Known to be a human carcinogen.

## **Reproductive toxicity**

No specific data.

### **Teratogenicity**

No specific data.

#### Specific target organ toxicity (single exposure)

No specific data.

## Specific target organ toxicity (repeated exposure)

No specific data.

#### **Aspiration hazard**

No specific data.

Information on the likely

routes of exposure

Not available.

### Potential acute health effects

**Eye contact** Causes serious eye irritation.

**Inhalation** No known significant effects or critical hazards.

**Skin contact** Causes skin irritation. May cause an allergic skin reaction.

**Ingestion** Irritating to mouth, throat and stomach.

## Symptoms related to the physical, chemical and toxicological characteristics

**Eye contact** Adverse symptoms may include the following:

pain or irritation watering redness

**Inhalation** No specific data.

**Skin contact** Adverse symptoms may include the following:

irritation redness

**Ingestion** No specific data.

### Delayed and immediate effects and also chronic effects from short and long term exposure

**Short term exposure** 

Potential immediate Not available.

effects

Potential delayed effects Not available.

**Long term exposure** 

Potential immediate Not available.

effects

Potential delayed effects Not available.

Potential chronic health effects

No specific data.

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 7/11

# **Section 11. Toxicological information**

General Once sensitized, a severe allergic reaction may occur when subsequently exposed to

very low levels.

CarcinogenicityNo known significant effects or critical hazards.MutagenicityNo known significant effects or critical hazards.TeratogenicityNo known significant effects or critical hazards.Developmental effectsNo known significant effects or critical hazards.Fertility effectsNo known significant effects or critical hazards.

## **Numerical measures of toxicity**

**Acute toxicity estimates** 

No specific data.

# Section 12. Ecological information

### **Toxicity**

No specific data.

## Persistence and degradability

No specific data.

#### **Bioaccumulative potential**

Product/ingredient name	LogPow	BCF	Potential
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin	2.64 to 3.78	31	low

#### **Mobility in soil**

Soil/water partition coefficient (Koc)

Not available.

#### Other adverse effects

No known significant effects or critical hazards.

# Section 13. Disposal considerations

### **Disposal methods**

The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

and sewe

Not applicable.

**RCRA** classification

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 8/11

# **Section 14. Transport information**

	DOT Classification	TDG Classification	Mexico Classification	IMDG	IATA
UN Number	Not regulated.	Not regulated.	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-	-	-
Transport hazard class(es)	-	-	-	-	-
Packing group	-	-	-	-	-
Environmental hazards	No.	No.	No.	No.	No.
Additional information	-	-	-	-	-

Special precautions for user

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

## Section 15. Regulatory information

U.S. Federal regulations TSC

TSCA 4(a) final test rules: di-"isodecyl" phthalate

TSCA 8(a) PAIR: Siloxanes and Silicones, di-Me, reaction products with silica

TSCA 8(a) CDR Exempt/Partial exemption: Not determined

United States inventory (TSCA 8b): All components are listed or exempted.

Clean Water Act (CWA) 307: di-"isodecyl" phthalate

Clean Air Act Section 112

(b) Hazardous Air Pollutants (HAPs)

Not listed

**Clean Air Act Section 602** 

Class I Substances

Not listed

**Clean Air Act Section 602** 

Not listed

**Class II Substances** 

**SARA 302/304** 

Composition/information on ingredients

No products were found.

SARA 304 RQ

Not applicable.

**SARA 311/312** 

Classification Immediate (acute) health hazard

Composition/information on ingredients

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 9/11

## Section 15. Regulatory information

Name	%	Fire hazard	Sudden release of pressure	Reactive	Immediate (acute) health hazard	Delayed (chronic) health hazard
reaction product: bisphenol-A- (epichlorhydrin); epoxy resin	10 - 30	No.	No.	No.	Yes.	No.
crystalline silica non-respirable	0.1 - 1	No.	No.	No.	No.	Yes.

**State regulations** 

Massachusetts The following components are listed: SOAPSTONE; CALCIUM CARBONATE;

TITANIUM DIOXIDE

**New York** None of the components are listed.

New Jersey The following components are listed: SOAPSTONE; SILICA, QUARTZ; QUARTZ

(SiO2); CALCIUM CARBONATE; LIMESTONE; TITANIUM DIOXIDE; TITANIUM

OXIDE (TiO2)

Pennsylvania The following components are listed: SOAPSTONE DUST; QUARTZ (SIO2);

LIMESTONE; TITANIUM OXIDE (TIO2)

Minnesota Hazardous Substances

California Prop. 65

None of the components are listed.

WARNING: This product contains a chemical known to the State of California to cause cancer.

**WARNING:** This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

Ingredient name	Cancer	Reproductive	No significant risk level	Maximum acceptable dosage level
Talc , not containing asbestiform fibres	Yes.	No.	No.	No.
titanium dioxide	Yes.	No.	No.	No.
crystalline silica non-respirable	Yes.	No.	No.	No.
di-"isodecyl" phthalate	No.	Yes.	No.	Yes.
carbon black respirable	Yes.	No.	No.	No.

**Canada inventory** 

All components are listed or exempted.

#### **International regulations**

International lists

**Australia inventory (AICS)**: All components are listed or exempted. **China inventory (IECSC)**: All components are listed or exempted.

Japan inventory: Not determined.

**Korea inventory**: All components are listed or exempted. **Malaysia Inventory (EHS Register)**: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined. Philippines inventory (PICCS): All components are listed or exempted.

Taiwan inventory (CSNN): Not determined.

#### Substances of very high concern

None of the components are listed.

## Section 16. Other information

**Key to abbreviations** ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships,

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 10/11

INSTACRETE 7 INCH EPOXY STICK

## **Section 16. Other information**

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

**UN = United Nations** 

References Not available.

**▼** Indicates information that has changed from previously issued version.

### **Notice to reader**

NON-WARRANTY: The information presented in this publication is based upon the research and experience of Whitford. No representation or warranty is made, however, concerning the accuracy or completeness of the information presented in this publication. Whitford makes no warranty or representation of any kind, express or implied, including without limitation any warranty of merchantability or fitness for any particular purpose, and no warranty or representation shall be implied by law or otherwise. Any products sold by Whitford are not warranted as suitable for any particular purpose to the buyer. The suitability of any products for any purpose particular to the buyer is for the buyer to determine. Whitford assumes no responsibility for the selection of products suitable to the particular purposes of any particular buyer. Whitford shall in no event be liable for any special, incidental, or consequential damages.

Date of issue/Date of revision 5 January 2015 Date of previous issue No previous validation. Version 1 11/11