## MATERIAL SAFETY DATA SHEET

COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29CFR 1910.1200)

## SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: I PRODUCT NUMBER: 501 PRODUCT TYPE: AEROSOL PPLIER'S NAME: C PPLIER'S ADDRESS: 4 INVADE

CHEMPACE CORPORATION

45 BURBANK TOLEDO, OH 43607 D.O.T. HAZARD CLASS: ORM-D

Chemical Family: N/A Formula: Proprietary Date Prepared: 6/16/94 HMIS RATING: (Based on Aerosol Concentrate): 0-Minimal; 1-Slight; 2-Moderate; 3-Serious; 4-Extreme

Emergency Phone: 419/535-0101 Information Phone: 419/535-0101

HEALTH ..... FIRE REACTIVITY ..... PERSONAL PROTECTION:

SECTION II - INGREDIENTS							
CHEMICAL NAME	CAS NO.	% WT	313/CHEM	PEL	SKIN	TWA-TLV	CARCINOGEN
Mineral Spirits Mineral Oil 1-Hexadecene & 1-Octadecene Oxygenated Hydrocarbon Blend Polyletralluoroethylene	64742-88-7 64741-89-5 68855-60-7 N/A 9002-84-0	80-100 1-5 Trace 1-5 Trace	NO NO NO NO	100 ppm N/E N/E N/E 10 mg/m³	NO NO NO NO	100 ppm N/E N/E N/E N/E 10 mg/m³	NO NO NO NO
Carbon Dioxide Propellant	124-38-9	1-5	МО	10000 ppm	NO	10000 ppm	NO

# SECTION III - PHYSICAL DATA

DATA BELOW BASED ON AEROSOL CONCENTRATE ONLY:

Boiling Point: N/D
Vapor Density (Air=1): >1
Solubility in Water: Slight
pH: N/A

Specific Gravity (H<sub>2</sub>O = 1) @ 75°F: 0.755

DATA BELOW BASED ON TOTAL CONTENTS:

Vapor Pressure of Can (psig @ 70°F): 70 Appearance/Odor : Dark Gray Liquid, Solvent Odor

#### SECTION IV - FIRE AND EXPLOSION DATA

Flash Point (OF CONCENTRATE ONLY): N/D Flammability as per USA Flame Projection Test: Extremely Flammable Spray Extinguishing Media: Foam, CO2, Dry Media

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards: Exposure to temperatures above 120°F may cause bursting.

#### SECTION V- REACTIVITY DATA

Stability: Stable Hazardous Polymerization; Will Not Occur

Incompatibility: Avoid contact with strong oxidizing agents
Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide

#### SECTION VI - STORAGE AND HANDLING

KEEP OUT OF THE REACH OF CHILDREN

For Industrial & Institutional Use Only. Store in a cool, dry area away from heat or open flame.

Do not store at temperatures above 120°F.

NFPA Code 30B Rating: Level 2 Aerosol

#### SECTION VII - HEALTH AND FIRST AID

#### PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE

EYES: May cause slight irritation but does not injure eye tissue.

SKIN: Frequent or prolonged contact may cause irritation

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea, and other central nervous system effects

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis. Minimal toxicity.

#### FIRST AID PROCEDURES

EYES: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN: Wash with soap and water. If irritation persists seek medical attention.

INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

## SECTION VIII - SPECIAL PROTECTION DATA

RESPIRATORY PROTECTION: None needed for proper use in accordance with label directions.

VENTILATION: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

PROTECTIVE GLOVES: None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.

EYE PROTECTION: None needed unless it is anticipated that a splash or sprayback will occur, then wear safety glasses.

## SECTION IX - SPILL OR LEAK PRECAUTIONS

# STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

Allow propellant to evaporate,

Maintain local exhaust and adequate ventilation.

No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

## WASTE DISPOSAL METHOD:

Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

#### N/A=NOT APPLICABLE N/E=NOT ESTABLISHED N/D=NOT DETERMINED <=LESS THAN >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor ly adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance aquirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.