

1 Identification

- **Product identifier**
- **Trade name: 80-148, 80-1212, 80-1213 / Torque-Lok Pipe Sealant with PTFE**
- **Application of the substance / the mixture** Adhesive
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Kimball Midwest
4800 Roberts Road
Columbus, OH 43228
Corporate Telephone: 800.233.1294
Emergency Telephone: Chemtrec 1.800.424.9300
- **Information department:** Product safety department
- **Emergency telephone number:** Emergency Telephone: Chemtrec 1.800.424.9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS07

- Acute Tox. 4 H302 Harmful if swallowed.
- Acute Tox. 4 H332 Harmful if inhaled.
- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2A H319 Causes serious eye irritation.
- Skin Sens. 1 H317 May cause an allergic skin reaction.
- STOT SE 3 H335 May cause respiratory irritation.

- **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Harmful

- Harmful if swallowed.

- **Information concerning particular hazards for human and environment:**
The product has to be labeled due to the calculation procedure of international guidelines.
- **Classification system:**
The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

- **Label elements**

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

- Polyethylene Glycol 200 Monooleate
- Polyethylene Glycol 200 Dimethacrylate
- α,α -dimethylbenzyl hydroperoxide
- Cellulose Acetate Butyrate

- **Hazard statements**

- Harmful if swallowed or if inhaled.
- Causes skin irritation.
- Causes serious eye irritation.
- May cause an allergic skin reaction.
- May cause respiratory irritation.

- **Precautionary statements**

- If medical advice is needed, have product container or label at hand.

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/15/2014

Reviewed on 11/21/2014

Trade name: 80-148, 80-1212, 80-1213 / Torque-Lok Pipe Sealant with PTFE

(Contd. of page 1)

Keep out of reach of children.
 Read label before use.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wear protective gloves.
 Wear eye protection / face protection.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Specific treatment (see on this label).
 If swallowed: Call a poison center/doctor if you feel unwell.
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Wash contaminated clothing before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Rinse mouth.
 If on skin: Wash with plenty of water.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a dry place.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	1	Fire = 1
REACTIVITY	0	Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**

- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

· Dangerous components:		
	Polyethylene Glycol 200 Dimethacrylate	25-50%
9004-96-0	Polyethylene Glycol 200 Monooleate	25-50%
9004-36-8	Cellulose Acetate Butyrate	2.5-<10%
80-15-9	α,α -dimethylbenzyl hydroperoxide	0.1-<1%

4 First-aid measures

· **Description of first aid measures**

· **General information:**

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Call a doctor immediately.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/15/2014

Reviewed on 11/21/2014

Trade name: 80-148, 80-1212, 80-1213 / Torque-Lok Pipe Sealant with PTFE

(Contd. of page 2)

- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

Components with limit values that require monitoring at the workplace:

80-15-9 α,α -dimethylbenzyl hydroperoxide

WEEL	Long-term value: 6 mg/m ³ , 1 ppm
	Skin

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Wash hands before breaks and at the end of work.
- **Breathing equipment:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.
- **Protection of hands:**
The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/15/2014

Reviewed on 11/21/2014

Trade name: 80-148, 80-1212, 80-1213 / Torque-Lok Pipe Sealant with PTFE

(Contd. of page 3)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:** Goggles recommended during refilling.

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Liquid
Color: According to product specification

- **Odor:** Characteristic

- **Odour threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: > 149 °C (> 300 °F)

- **Flash point:** > 94 °C (> 201 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:**

Decomposition temperature: Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

Lower: Not determined.

Upper: Not determined.

- **Vapor pressure:** Not determined.

- **Density:** Not determined.

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

- **Viscosity:**

Dynamic: Not determined.

Kinematic: Not determined.

- **Solvent content:**

Organic solvents: 0.0 %

Water: 0.2 %

- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity**

- **Chemical stability**

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/15/2014

Reviewed on 11/21/2014

Trade name: 80-148, 80-1212, 80-1213 / Torque-Lok Pipe Sealant with PTFE

(Contd. of page 4)

- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)		
9002-84-0	Polytetrafluoroethylene	3
13463-67-7	titanium dioxide	2B
81-07-2	1,2-benzisothiazol-3(2H)-one 1,1-dioxide	3
7631-86-9	silicon dioxide, chemically prepared	3
98-82-8	cumene	2B
98-83-9	2-phenylpropene	2B

- **NTP (National Toxicology Program)**

98-82-8	cumene	R
---------	--------	---

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADN, IMDG, IATA** Void

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/15/2014

Reviewed on 11/21/2014

Trade name: 80-148, 80-1212, 80-1213 / Torque-Lok Pipe Sealant with PTFE

(Contd. of page 5)

· UN proper shipping name	
· DOT, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· DOT, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· DOT, IMDG, IATA	Void
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	-

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

81-07-2	1,2-benzisothiazol-3(2H)-one 1,1-dioxide
80-15-9	α,α -dimethylbenzyl hydroperoxide
98-82-8	cumene
98-86-2	acetophenone

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

13463-67-7	titanium dioxide
98-82-8	cumene
98-83-9	2-phenylpropene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

98-82-8	cumene	D, CBD
98-86-2	acetophenone	D

· TLV (Threshold Limit Value established by ACGIH)

13463-67-7	titanium dioxide	A4
------------	------------------	----

· NIOSH-Ca (National Institute for Occupational Safety and Health)

13463-67-7	titanium dioxide
------------	------------------

- GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/15/2014

Reviewed on 11/21/2014

Trade name: 80-148, 80-1212, 80-1213 / Torque-Lok Pipe Sealant with PTFE

(Contd. of page 6)

- **Hazard pictograms**



GHS07

- **Signal word** Warning

- **Hazard-determining components of labeling:**

Polyethylene Glycol 200 Monooleate
 Polyethylene Glycol 200 Dimethacrylate
 α, α -dimethylbenzyl hydroperoxide
 Cellulose Acetate Butyrate

- **Hazard statements**

Harmful if swallowed or if inhaled.
 Causes skin irritation.
 Causes serious eye irritation.
 May cause an allergic skin reaction.
 May cause respiratory irritation.

- **Precautionary statements**

If medical advice is needed, have product container or label at hand.
 Keep out of reach of children.
 Read label before use.
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Wear protective gloves.
 Wear eye protection / face protection.
 Wash thoroughly after handling.
 Do not eat, drink or smoke when using this product.
 Use only outdoors or in a well-ventilated area.
 Contaminated work clothing must not be allowed out of the workplace.
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 Specific treatment (see on this label).
 If swallowed: Call a poison center/doctor if you feel unwell.
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 Wash contaminated clothing before reuse.
 If skin irritation or rash occurs: Get medical advice/attention.
 If eye irritation persists: Get medical advice/attention.
 Rinse mouth.
 If on skin: Wash with plenty of water.
 Take off contaminated clothing and wash it before reuse.
 Store locked up.
 Store in a well-ventilated place. Keep container tightly closed.
 Store in a dry place.
 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Environment protection department.

- **Contact:** Kimball Midwest Regulatory

- **Date of preparation / last revision** 12/15/2014 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/15/2014

Reviewed on 11/21/2014

Trade name: 80-148, 80-1212, 80-1213 / Torque-Lok Pipe Sealant with PTFE

(Contd. of page 7)

HMIS: Hazardous Materials Identification System (USA)
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3