

Revision Date 09-Mar-2015

Version 1

SAFETY DATA SHEET

1. IDENTIFICATION		
Dreduct identifier		
Product identifier Product Name	THE RIGHT STUFF GASKET MAKER 4 OZ AE	
Product Name	THE RIGHT STUFF GASKET MAKER 4 02 AE	
Other means of identification		
Product Code	25223	
Synonyms	None	
eyey		
Recommended use of the chemica	and restrictions on use	
Recommended Use	Sealant	
Uses advised against	No information available	
-		
Details of the supplier of the safety	y data sheet	
Manufacturer Address	Distributor	
ITW Permatex	ITW Permatex Canada	
10 Columbus Blvd.	35 Brownridge Road, Unit 1	
Hartford, CT 06106 USA	Halton Hills, ON Canada L7G 0C6	
	Telephone: (800) 924-6994	
Company Phone Number	1-87-Permatex	
company i none Number	(877) 376-2839	
24 Hour Emergency Phone Number		
24 Hour Emergency Flione Numbe	International Emergency:	
	00+1+813-248-0585	
	Contract Number: MIS0003453	

2. HAZARDS IDENTIFICATION

Classification

OSHA Regulatory Status

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Serious eye damage/eye irritation	Category 2A
Skin sensitization	Category 1
Carcinogenicity	Category 2

Label elements

Emergency Overview

Warning

Causes serious eye irritation May cause an allergic skin reaction Suspected of causing cancer



Appearance Black

Physical state Paste

Odor Mild

Precautionary Statements - Prevention

Obtain special instructions before use Do not handle until all safety precautions have been read and understood Use personal protective equipment as required Wash face, hands and any exposed skin thoroughly after handling Avoid breathing dust/fume/gas/mist/vapors/spray Contaminated work clothing should not be allowed out of the workplace Wear protective gloves/protective clothing/eye protection/face protection

Precautionary Statements - Response

IF exposed or concerned: Get medical advice/attention IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing If eye irritation persists: Get medical advice/attention IF ON SKIN: Wash with plenty of soap and water If skin irritation or rash occurs: Get medical advice/attention Wash contaminated clothing before reuse

Precautionary Statements - Storage

Store locked up

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Other Information

Harmful to aquatic life with long lasting effects

Unknown acute toxicity

10.294% of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Chemical Name	CAS No	Weight-%	Trade Secret
CALCIUM CARBONATE	471-34-1	15 - 40	*
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED	70131-67-8	15 - 40	*
POLYDIMETHYLSILOXANE	63148-62-9	7 - 13	*
VINYL OXIMINOSILANE	2224-33-1	1 - 5	*
NITROGEN	7727-37-9	1 - 5	*
STEARIC ACID	57-11-4	1 - 5	*
CARBON BLACK	1333-86-4	1 - 5	*
2-BUTANONE OXIME	96-29-7	1 - 5	*

*The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures	
General advice	Get medical advice/attention if you feel unwell.
Eye contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Skin contact	IF ON SKIN:. Wash with soap and water. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, call a physician.
Ingestion	IF SWALLOWED. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.
Self-protection of the first aider	Use personal protective equipment as required.
Most important symptoms and effe	cts, both acute and delayed
Symptoms	May cause redness and tearing of the eyes. May cause allergic skin reaction.
Indication of any immediate medica	al attention and special treatment needed
Note to physicians	Treat symptomatically.
	5. FIRE-FIGHTING MEASURES
Suitable extinguishing media Carbon dioxide (CO2), Dry chemical,	Foam
<u>Unsuitable extinguishing media</u> None.	
Specific hazards arising from the c Heating causes rise in pressure with	hemical isk of bursting. Keep product and empty container away from heat and sources of ignition.
<u>Explosion data</u> Sensitivity to Mechanical Impact Sensitivity to Static Discharge	None. None.
Protective equipment and precauti As in any fire, wear self-contained bre protective gear.	ons for firefighters eathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full
	6. ACCIDENTAL RELEASE MEASURES
Personal precautions, protective e	quipment and emergency procedures
Personal precautions	Ensure adequate ventilation, especially in confined areas. Avoid contact with eyes and skin. Remove all sources of ignition. Do not puncture or incinerate cans.
Environmental precautions	
Environmental precautions	Do not flush into surface water or sanitary sewer system. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
Methods and material for containm	ent and cleaning up
Methods for containment	Prevent further leakage or spillage if safe to do so.

Description of first aid measures

Methods for cleaning up	Ensure adequate ventilation. Flood with water to complete polymerization and scrape off floor. Sweep up and shovel into suitable containers for disposal. Slippery, can cause falls if walked on.
Prevention of secondary hazards	Clean contaminated objects and areas thoroughly observing environmental regulations.
	7. HANDLING AND STORAGE
Precautions for safe handling	
Advice on safe handling	Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Use personal protective equipment as required.
Conditions for safe storage, including	ng any incompatibilities
Storage Conditions	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Protect from moisture.
Incompatible materials	Strong oxidizing agents, Acids, Water

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
CALCIUM CARBONATE 471-34-1	-	-	TWA: 10 mg/m ³ total dust TWA: 5 mg/m ³ respirable dust
CARBON BLACK 1333-86-4	TWA: 3 mg/m ³ inhalable fraction	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH

NIOSH IDLH Immediately Dangerous to Life or Health

Other InformationVacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962
(11th Cir., 1992).

Appropriate engineering controls

Engineering Controls	Showers
	Eyewash stations Ventilation systems
	ventilation systems

Individual protection measures, such as personal protective equipment

Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin and body protection	Wear protective gloves and protective clothing.
Respiratory protection	Use NIOSH-approved air-purifying respirator with organic vapor cartridge or canister, as appropriate.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice. Regular cleaning of equipment, work area and clothing is recommended.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Appearance Odor Odor threshold	Paste Black Mild No information available	
<u>Property</u>	Values	Remarks • Method
рН	7-8	
Melting point / freezing point	No information available	
Boiling point / boiling range	Not Applicable	Polymerization
Flash point	> 93 °C / > 199 °F	Tag Closed Cup
Evaporation rate	< 1	Butyl acetate = 1
Flammability (solid, gas)	No information available	
Flammability Limit in Air		
Upper flammability limit:	No information available	
Lower flammability limit:	No information available	
Vapor pressure	<5 mmHg @ 70°F	
Vapor density	3	Air = 1
Relative density	1.34	
Water solubility	Not applicable	Polymerization
Solubility in other solvents	No information available	
Partition coefficient	No information available	
Autoignition temperature	No information available	
Decomposition temperature	No information available	
Kinematic viscosity	No information available	
Dynamic viscosity	No information available	
Explosive properties	No information available	
Oxidizing properties	No information available	
Other Information		
Softening point Molecular weight VOC Content (%) Density Bulk density	No information available No information available <3% No information available No information available	
-		

10. STABILITY AND REACTIVITY

Reactivity No data available

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

Risk of explosion if heated under confinement.

Conditions to avoid

Heat, flames and sparks. Exposure to air or moisture over prolonged periods.

Incompatible materials

Strong oxidizing agents, Acids, Water

Hazardous Decomposition Products

Carbon oxides, Nitrogen oxides (NOx), Formaldehyde, May release 2-butanone oxime (ethyl methyl ketoxime) at elevated temperature

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Inhalation	May cause irritation of respiratory tract.
Eye contact	Contact with eyes may cause irritation. May cause redness and tearing of the eyes.
Skin contact	May cause skin irritation and/or dermatitis. May cause sensitization by skin contact.
Ingestion	Ingestion may cause irritation to mucous membranes.

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
CALCIUM CARBONATE 471-34-1	= 6450 mg/kg (Rat)	-	-
POLY (DIMETHYLSILOXANE), HYDROXY TERMINATED 70131-67-8	-	> 16 mL/kg (Rabbit)	> 8750 mg/m³(Rat)7 h
POLYDIMETHYLSILOXANE 63148-62-9	> 17 g/kg (Rat)	> 2 g/kg (Rabbit)	-
STEARIC ACID 57-11-4	-	> 5 g/kg (Rabbit)	-
CARBON BLACK 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
2-BUTANONE OXIME 96-29-7	= 930 mg/kg (Rat)	= 0.2 mg/kg (Rabbit)	= 20 mg/L (Rat)4 h

Information on toxicological effects

Symptoms

No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Serious eye damage/eye i		ous eye irritation.		
Sensitization	May cause s	May cause sensitization by skin contact. No information available.		
Germ cell mutagenicity	No informati			
Carcinogenicity	The table be	low indicates whether each	agency has listed any ing	gredient as a carcinogen
Chemical Name	ACGIH	IARC	NTP	OSHA
CARBON BLACK	A3	Group 2B	-	Х
1333-86-4				
ACGIH (American Confe	ence of Governmental Ind	dustrial Hygienists)		
A3 - Animal Carcinogen				
	cy for Research on Cance	er)		
Group 2B - Possibly Carcii				
	ety and Health Administra	ation of the US Department of	f Labor)	
OSHA (Occupational Saf X - Present Target Organ Effects		natic System, Respiratory sy		

The following values are calculated based on chapter 3.1 of the GHS document .ATEmix (oral)10960 mg/kgATEmix (dermal)8999 mg/kg

12. ECOLOGICAL INFORMATION

Ecotoxicity

None known

Chemical Name	Algae/aquatic plants	Fish	Crustacea
CARBON BLACK 1333-86-4	-	-	5600: 24 h Daphnia magna mg/L EC50
2-BUTANONE OXIME 96-29-7	83: 72 h Desmodesmus subspicatus mg/L EC50	777 - 914: 96 h Pimephales promelas mg/L LC50 flow-through 320 - 1000: 96 h Leuciscus idus mg/L LC50 static 760: 96 h Poecilia reticulata mg/L LC50 static	750: 48 h Daphnia magna mg/L EC50

Persistence and degradability

No information available.

Bioaccumulation

No information available.

Mobility

No information available.

Chemical Name	Partition coefficient
2-BUTANONE OXIME	0.65
96-29-7	

Other adverse effects

No information available

13. DISPOSAL CONSIDERATIONS

Waste treatment methods	
Disposal of wastes	Disposal should be in accordance with applicable regional, national and local laws and regulations.
Contaminated packaging	Do not reuse container.
US EPA Waste Number	Not applicable

14. TRANSPORT INFORMATION

	15. REGULATORY INFOR
IMDG UN/ID no Proper shipping name: Hazard Class EmS-No Special Provisions	UN 1950 Aerosols, Limited Quantity (LQ) 2.2 F-D, S-U 63, 190, 277, 327, 344, 959
IATA UN/ID no Proper shipping name: Hazard Class ERG Code Special Provisions	ID 8000 Consumer commodity 9 9L A112
DOT UN/ID no Proper shipping name: Hazard Class	UN 1950 Aerosols Limited Quantity (LQ) 2.2

RMATION

International Inventories	
TSCA	(
DSL/NDSL	(
EINECS/ELINCS	[
ENCS	[
IECSC	(
KECL	(

Complies Complies Does not comply Does not comply Complies Complies

PICCS AICS

Complies Complies

Leaend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances **ENCS** - Japan Existing and New Chemical Substances IECSC - China Inventory of Existing Chemical Substances KECL - Korean Existing and Evaluated Chemical Substances PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazard Categories

Acute health hazard	Yes
Chronic Health Hazard	No
Fire hazard	No
Sudden release of pressure hazard	No
Reactive Hazard	No

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals

Chemical Name	California Proposition 65
CARBON BLACK - 1333-86-4	Carcinogen

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
NITROGEN 7727-37-9	Х	X	X
CARBON BLACK 1333-86-4	Х	X	X
ALUMINIUM POWDER 7429-90-5	Х	X	X

U.S. EPA Label Information

NFPA (National Fire Protection Association) HMIS (Hazardous Material Information System)

EPA Pesticide Registration Number Not applicable

NFPAHealth hazards 2HMISHealth hazards 2	Flammability 2	Instability 0	-
	Flammability 2	Physical hazards 0	Persor

onal protection B

Revision Date

09-Mar-2015

Disclaimer

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet