

## SAFETY DATA SHEET

SDS 0223

=====  
Section 1 -- PRODUCT AND COMPANY IDENTIFICATION  
=====

	HMIS CODES
PRODUCT NAME K.O. Dirt Blaster (TM)	Health 2 Flammability 0 Reactivity 0
PRODUCT CODES 88438	PPI B
CHEMICAL FAMILY Organic	
USE Cleaner & Degreaser	
MANUFACTURER'S NAME The RectorSeal Corporation 2601 Spenwick Drive Houston, Texas 77055 USA	EMERGENCY TELEPHONE NO. Chemtrec 24 Hours (800)424-9300 USA (703)527-3887 International
DATE OF VALIDATION April 1, 2015	TECHNICAL SERVICE TELEPHONE NO. (800)231-3345 or (713)263-8001
DATE OF PREPARATION April 1, 2015	

=====  
Section 2 -- HAZARDS IDENTIFICATION  
=====

Emergency Overview  
OSHA Hazards  
Carcinogen, Target Organ Effect, Harmful by ingestion., Irritant  
Target Organs  
Liver, pancreas, Blood, Central nervous system, Heart, Kidney  
GHS Classification  
Acute toxicity, Oral (Category 4)  
Skin irritation (Category 2)  
Eye irritation (Category 2B)  
Carcinogenicity (Category 2)

GHS Label elements, including precautionary statements  
Pictogram: GHS08 Health hazard, GHS07 Exclamation mark, GHS04 Gas Cylinder  
Signal Word: Warning  
Hazard statement(s)  
H302 - Harmful if swallowed.  
H315 + H320 - Causes skin and eye irritation.  
H351 - Suspected of causing cancer.  
Precautionary statement(s)  
P281 - Use personal protective equipment as required.  
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes.  
Remove contact lenses, if present and easy to do. Continue rinsing.

=====  
SUMMARY OF ACUTE HAZARDS

Repeated inhalation may cause dizziness, nausea and CNS effects. May cause severe eye and skin irritation.

## ROUTE OF EXPOSURE, SIGNS AND SYMPTOMS

INHALATION

Inhalation of high concentrations may cause central nervous system effects characterized by headache, dizziness, drowsiness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

EYE CONTACT

Contact with eyes may cause severe irritation.

SKIN CONTACT

Irritation and drying.

INGESTION

May cause irritation of the digestive tract. May cause central nervous system depression, characterized by excitement, followed by headache, dizziness, and nausea. Advanced stages may cause collapse, unconsciousness, coma and possible death due to respiratory failure.

SUMMARY OF CHRONIC HAZARDS

Skin irritation, contact dermatitis, and defatting.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE

Individuals with pre-existing or chronic diseases of the eyes, skin, respiratory system, cardiovascular system, gastrointestinal system, liver, or kidneys may have increased susceptibility to excessive exposure.

=====  
Section 3 -- COMPOSITION/INFORMATION ON INGREDIENTS  
=====

-----  
INGREDIENT: Methylene Chloride

PERCENTAGE BY WEIGHT: --

CAS NUMBER: 75-09-2

EC# : 200-838-9  
=====

Section 4 -- FIRST AID MEASURES  
-----

If INHALED: If overcome by exposure, remove victim to fresh air immediately. Give oxygen or artificial respiration as needed. Obtain emergency medical attention. Prompt action is essential.

If on SKIN: Immediately wash with soap and water. Remove and wash any contaminated clothing.

If in EYES: Flush eyes with large amounts of water for 15 minutes. Get medical attention if irritation persists.

If SWALLOWED: If swallowed, call a physician immediately. Only induce vomiting at the instruction of a physician. Never give anything by mouth to an unconscious person.

=====  
Section 5 -- FIRE FIGHTING MEASURES  
=====

EXTINGUISHING MEDIA

Foam, dry chemical, CO2, or water fog.

SPECIAL FIRE FIGHTING PROCEDURES: Wear self-contained full face piece breathing apparatus and full body protective clothing. Hazardous decomposition products possible (see Section 10). Evacuate area. Dike area as run-off may create additional environmental contamination.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Aerosol cans are under pressure - exposure to temperatures above 120F can cause bursting or "rocketing" of cans.

=====  
Section 6 -- ACCIDENTAL RELEASE MEASURES  
=====

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Use absorbent materials to prevent footing hazard and to contain. Ventilate area with forced air ventilation. Avoid flushing into sewers, drains, waterways, and soil. Wear protective clothing and respiratory protection during cleanup.

---

Section 7 -- HANDLING AND STORAGE

---

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Shake well before using. Keep away from heat and open flames. Prolonged exposure to direct sunshine or storage above 120 F may cause can to burst. Do not puncture or incinerate can.

OTHER PRECAUTIONS: Avoid prolonged or repeated contact with skin or clothing.

Empty containers may contain residues; treat as if full and observe all products precautions.

---

Section 8 -- EXPOSURE CONTROLS/PERSONAL PROTECTION

---

INGREDIENT	UNITS
Methylene Chloride	
ACGIH TLV	50 ppm
OSHA PEL	25 ppm
OSHA STEL	125 ppm

---

RESPIRATORY PROTECTION (SPECIFY TYPE): In confined, poorly ventilated areas, use NIOSH/MSHA approved air purifying or supplied air respirators during soldering operations until fumes have dissipated.

VENTILATION - LOCAL EXHAUST: Acceptable

SPECIAL: Explosion proof

MECHANICAL (GENERAL): Acceptable

OTHER: N/A

PROTECTIVE GLOVES: Wear rubber gloves.

EYE PROTECTION: Safety glasses (ANSI Z-87.1 or equivalent)

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Chemical resistant coveralls recommended.

WORK/HYGIENIC PRACTICES: Where use can result in skin contact, wash exposed areas thoroughly before eating, drinking, smoking, or leaving work area. Launder contaminated clothing before reuse.

---

Section 9 -- PHYSICAL AND CHEMICAL PROPERTIES

---

BOILING POINT:	104 F (40 C) @ 760mm Hg
SPECIFIC GRAVITY (H2O = 1):	1.27
VAPOR PRESSURE (mm Hg):	350 mm HG @ 20 C
MELTING POINT:	N/A
VAPOR DENSITY (AIR = 1):	2.9
EVAPORATION RATE (ETHYL ACETATE = 1):	>1
APPEARANCE/ODOR:	Clear Liquid / Citrus Odor
SOLUBILITY IN WATER:	Insoluble
AEROSOL FLAME EXTENSION:	Negative
FLASH POINT:	None
LOWER EXPLOSION LIMIT:	N/D
UPPER EXPLOSION LIMIT:	N/D
VOLATILE ORGANIC COMPOUNDS (VOC) Content (Theoretical Percentage By Weight):	0% or 0 g/L (VOC Exempt)

---

Section 10 -- STABILITY AND REACTIVITY

STABILITY: Stable  
CONDITIONS TO AVOID: Do not store in temperatures above 120 F.  
INCOMPATIBILITY (MATERIALS TO AVOID): Oxidizers, acids and bases.  
HAZARDOUS DECOMPOSITION PRODUCTS: CO, CO, and fragmented hydrocarbons.  
HAZARDOUS POLYMERIZATION: Will not occur.

Section 11 -- TOXICOLOGY INFORMATION

CHRONIC HEALTH HAZARDS

No ingredient in this product is an IARC, NTP or OSHA listed carcinogen. Methylene chloride has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure.  
Carcinogenicity - rat - Inhalation  
Tumorigenic: Carcinogenic by RTECS criteria. Endocrine: Tumors.  
Limited evidence of carcinogenicity in animal studies  
IARC: 2B - Group 2B: Possibly carcinogenic to humans (Methylene chloride)  
NTP: Reasonably anticipated to be a human carcinogen (Methylene chloride)

TOXICOLOGY DATA

Ingredient Name

Methylene Chloride

Oral-Rat LD50: 1600 mg/kg  
Inhalation-Rat LC50: 88,000 mg/m<sup>3</sup>/30M

Section 12 -- Ecological Information

ECOLOGICAL DATA

Ingredient Name

Methylene Chloride

Food Chain Concentration Potential	None
WATERFOWL TOXICITY	N/A
BOD	N/A
AQUATIC TOXICITY	N/A

Section 13 -- DISPOSAL CONSIDERATIONS

Waste Classification: Aerosols  
Disposal Method: Empty containers can be disposed of in trash. Full containers should be depressurized to separate liquid phase. The liquid phase is considered a U080 waste and should be incinerated. Dispose of all liquid waste in accordance with all local, state and federal regulations.

Section 14 -- TRANSPORTATION INFORMATION

DOT: UN1950, Aerosols, Class 2.2, ERG#126  
OCEAN (IMDG): UN1950, Aerosols, Class 2.2, LTD-QTY, EMS-No: F-A, S-A  
AIR (IATA): UN1950, Aerosols, Class 2.2, ERG#126  
WHMIS (CANADA): Class A, (Class D Division 1, Subdivision B)

Section 15 -- REGULATORY INFORMATION

REGULATORY DATA

Ingredient Name

---

Methylene Chloride

SARA 313	Yes
TSCA Inventory	Yes
CERCLA RQ	1000 lbs.
RCRA Code	U080

---

CALIFORNIA PROPOSITION 65

This product contains methylene chloride known to the state of California to cause cancer and/or birth defects or reproductive harm.

---

---

Section 16 -- OTHER INFORMATION

---

This document is prepared pursuant to the OSHA Hazard Communication Standard (29 CFR 1910.1200). The information herein is given in good faith, but no warranty, expressed or implied is made. Consult RectorSeal for further information: (713) 263-8001