QUICKCRETE Concrete Repair Epoxy Putty

HMIS RATING	
Health	1
Flammability	1
Reactivity	0

MATERIAL SAFETY DATA SHEET

NFPA 704 RA	<u> FING</u>
Health	N/A
Flammability	N/A
Reactivity	N/A
NFPA 30B LEVEL	
N/A	

Kimball-Mktwest P.O. Box 2470 Columbus, OH 43216-2470 Corporate & Emergency Telephone (614-228-6701)

1	PRO	DUCT	IDENTII	FICATION

PART NUMBER	80-202
PRODUCT NAME	QUICKCHETE Conrete Repair Epoxy Putty
CHEMICAL FAMILY	
DOT SHIPPING	Not regulated

2. HAZARDOUS INGREDIENTS

Specific chamical identity, common names	OSHA PEL ACGIH TLV STEL	9
Glyddyl Ethers of		
Bisphenol A Resins (25068-38-6)	Not Established	14
Trl (dimethylaminoethyl) phenol (90-72-2)	Not Established	0
Additional Company of the Company of	i	

Bisphenol A F 4.0 Trl (dimethylam 8.0 Magnesium Silicate Hydrale (14807-96-6) Polyelher Polymercaptan (trade secret) Caldum Carbonale (1317-65-3) Silica (7631-86-9) 2.7 *Zinc Compounds (NA) Proprietary Items

All chemical compounds marked with an asterisk (*) are toxic chemicals subject to the reporting requirements of Section 313 of Tale III of the Superfund Amendments and Reauthorization Act (SARA) of 1988 and 40 CFR Part 372. You must notify each person to whom this mixture of trade name product is sold. This statement must not be detached. Any copy or redistribution of this Malerial Safety Data Sheet shall include this statement.

3. PHYSICAL DATA

BOILING POINT (RANGE)	N/A
VAPOR PRESSURE PSIG 0 70 F	N/A
VAPOR DENSITY (Air = 1)	Non Volatile
SOLUBILITY IN WATER	Negligible
SPECIFIC GRAVITY (H2O = 1	Heavler than water
WEIGHT PER GALLON	16,30 Pounds
MELTING/FREEZING POINT	NA
EVAPORATION RATE (n-Butyl Acatale= 1)	0.0
VOLATILES (volume)	0%
APPEARANCE AND ODOR	

4. FIRE AND EXPLOSION DATA

FLASH POINT	N/A TOC
UPPER EXPLOSIVE LIMIT (%)	None
LOWER EXPLOSIVE LIMIT (%)	None
EXTINGUISHING MEDIA	
	CO ₂ .
SPECIAL FIREFIGHTING PROCEDURES	Fire(ighters should wear NIOSH
	approved positive pressure self-
	contained breathing apparatus.
FIRE AND EXPLOSION HAZARDS	
	sulfur & nitrogen may be formed.
NFPA FLAMMABILITY HAZARD	N/A

5. HEALTH EFFECTS DATA

SHORT TERM EFFECTS OF EXPOSURE

ROUTE OF ENTRY......Skin, Eyes, Ingestion, Inhalation

SIGNS AND SYMPTOMS

OF OVEREXPOSUREInhalation: None

Ingestion: irritation of intestinal tract. Skin Contact: Possible Initant and sensitizer. Eye Contact: Possible Initiant and sensitizer.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSUREN/A

5. HEALTH EFFECTS DATA (Continued)

FIRST AID PROCEDURES

EYES	Flush with water for at least 15 minutes. Obtain
	medical attention.
SKIN CONTACT	Wash with soap and water.
INHALATION	N/A
INGESTION	Induce vemiller. Call a physician immediately.

SPECIAL HEALTH EFFECTS

CARCINOGEN (OSHA Guidelines).....N/A

6. REACTIVITY

STABILITY	Stable
INCOMPATIBILITIES	Nona
NFPA REACTIVITY HAZARD	N/A
HAZARDOUS DECOMPOSITION	
PRODUCTS	CO, aldehydes, acids, oxides of
	sullur & nitrogen.
HAZARDOUS POLYMERIZATION	
HAZARDOUS POLYMERIZATION (CONDITIONSNone known.
E	

7. PRECAUTIONS FOR SAFE HANDLING AND USE

PROTECTIVE EQUIPMENT	
р М L	Salety glasses or goggles. Protective polyethylene gloves for prolonged use. No respiratory protection required. Local exhaust only if heated above 100°F.
	Wash with soap and water Immediately after use.
	Dispose of in normal manner, not a nazardous waste.
	ncinerate in furnace or bury in landfill according to applicable regulations.
	Avold eye contact and excessive skin contact.
8.	Wash with soap and water immedialely uiter use, if sanding cured pulty or substrates, wear eye protection and hist mask

8. ADDITIONAL INFORMATION

Use self contained breathing apparatus # TLV limits are exceeded. Do not smoke while using. Wash hands after use. THE INFORMATION GIVEN AND THE RECOMMENDATIONS MADE HEREIN APPLY TO OUR PRODUCT(S) ALONE AND ARE NOT COMBINED WITH OTHER PRODUCT(S), SUCH ARE BASED ON OUR RESEARCH AND ON DATA FROM OTHER RELIABLE SOURCES AND ARE BELIEVED TO BE ACCURATE. NO GUARANTEE OF ACCURACY IS MADE. IT IS THE PURCHASER'S RESPONSIBILITY BEFORE USING ANY PRODUCT TO VERIFY THIS DATA UNDER THEIR OWN OPERATION CONDITIONS AND TO DETERMINE WHETHER THE PRODUCT IS SUITABLE FOR THEIR PURPOSES.



Your Partner in Performance

COPYRIGHT = 12/95