

CHEWING GUM REMOVER #CA002

Material Safety Data Sheet

Quick Identifier (In Plant Common Name)

Manufactured For: PRO-LINK, INC.
Name & Address: CANTON, MA 02021

Emergency: 1-800.74.LINKS Mon. - Fri. 8-5
Telephone No. (800) 255-3924 24 HOURS

Date Prepared: June 3, 2002


Prepared By:

Date:

HMIS Symbol:

Health	1
Flammability	4
Reactivity	0

HMIS — NFPA
Minimal - 0 - Insignificant
Slight - 1 - Slight
Moderate - 2 - Moderate
Serious - 3 - High
Severe - 4 - Extreme

NFPA Symbol:**SECTION 1 - IDENTITY**

Common Name: (used on label) Chewing Gum Remover #CA002
(Trade name & Synonyms)

Chemical Name: Mixture packaged in pressurized aerosol spray container.

SECTION 2 - HAZARDOUS INGREDIENTS

Principal Hazardous Component(s)	CAS No.	OSHA PEL	ACGIH TLV	Other Limits
Propane	74-98-6	Not Est.	1,000 ppm	
Butane	106-97-8	Not Est.	800 ppm	

*Section 313 Supplier Notification - Indicates hazardous ingredients which are toxic chemicals subject to the reporting requirements of Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

SECTION 3 - PHYSICAL & CHEMICAL CHARACTERISTICS

Boiling Point	-6.4 to +10.9°F	Specific Gravity (H ₂ O=1)	0.566	Vapor Pressure (PSI)	44 - 46
Volatile Organic Content (% Weight)	100%	Evaporation Rate	Immediate at temperatures above -6.4°F.		
Solubility In Water	None	Appearance and Odor	Liquid - clear; Vapor - not visible; Odor - sweet petroleum.		

SECTION 4 - FIRE & EXPLOSION DATA

Flammability (per flame projection)	Extremely Flammable	Flammable Limits in Air % by Volume	Lower 1.8%	Upper 9.5%	Extinguisher Media	Dry Chemical (B-C), H ₂ O
-------------------------------------	---------------------	-------------------------------------	------------	------------	--------------------	--------------------------------------

Special Fire Fighting Procedures: Keep containers cool using water spray. Use proper equipment to

protect personnel from bursting containers. Extinguish ALL sources of ignition.

Unusual Fire and Explosion Hazards: Contents under pressure. Do not expose to temperatures exceeding 120°F. as containers may vent, rupture or burst. Vapors are heavier than air and may travel along the ground or may be moved by ventilation systems and ignited by pilot lights, other flames, sparks, heaters, smoking, electric motors, static discharge, or other ignition sources at locations distant from material handling point.

SECTION 5 - PHYSICAL HAZARDS

Stability	Unstable ☐ Conditions High heat, spark, Hazardous May Occur ☐ Conditions to Avoid None
	Stable ☒ to Avoid and open flames. Polymerization Will not Occur ☒ to Avoid

Incompatibility (Materials to Avoid): None.

Hazardous Decomposition Products: Carbon Monoxide, Volatile Hydrocarbon Vapors

SECTION 6 - HEALTH HAZARDS

Routes of Entry Inhalation: Yes Eyes / Skin: Yes Ingestion: Unlikely

Signs and Symptoms of Exposure (Acute & Chronic) Liquid can cause freeze burns and irritation in contact with skin and eyes.

Aspiration hazard: Vapor inhalation has effects of anesthetic or euphoria.

Medical Conditions Generally Aggravated by Exposure None Known

Chemical Listed as Carcinogen or Potential Carcinogen National Toxicology Program Yes ☐ No ☒ I.A.R.C. Monographs Yes ☐ No ☒ OSHA Yes ☐ No ☒

Emergency and First Aid Procedures

1. Inhalation Remove victim to fresh air. Apply artificial respiration if necessary. Get medical attention.

2. Eyes Flush eyes with water for at least 15 minutes. Get medical attention immediately.

3. Skin Warm affected areas gradually. Flush areas with plenty of water. Get medical attention if there is evidence of tissue damage.

4. Ingestion Do not induce vomiting. Get medical attention immediately.

SECTION 7 - SPECIAL PROTECTION INFORMATION

Respiratory Protection (Specify Type) None required for normal use.

Ventilation Local Exhaust Maintain adequate ventilation Mechanical (General) N/A Special N/A Other N/A

Protective Gloves Not required for normal use. Eye Protection None required for normal use.

Other Protective Clothing or Equipment None required.

SECTION 8 - SPECIAL PRECAUTIONS AND SPILL/LEAK PROCEDURES

Precautions to be Taken Handling and Storage Do not store at temperatures above 120°F. Do not puncture or incinerate containers. Keep out of reach of children. Store in accordance with NFPA 30B for Level 3 Aerosols.

Other Precautions Read label precautions carefully. Do not smoke during use. Do not use near sparks or flame.

Steps to be Taken in Case Material is Released or Spilled Avoid sources of ignition - Ventilate area. Use water fog to evaporate or ventilate. Protect body against contact with liquid. If confined space - use self contained breathing apparatus. Consult local fire authorities.

Waste Disposal Methods Dispose of in accordance with local, state, and federal regulations.

We believe all information given is accurate. It is offered in good faith, but without guarantee. Since conditions are beyond our control, user assumes all responsibility and risk.