

MATERIAL SAFETY DATA SHEET
U.S. DEPARTMENT OF LABOR
COMPLIES WITH USDL SAFETY AND HEALTH REGULATIONS. (29 CFR 1910.1200)
IMPORTANT! THIS IS YOUR ONLY COPY. PLEASE DISTRIBUTE TO ALL PLANT LOCATIONS
CODE #:5359 REV: 002
DATE SENT: 11/26/01

SECTION I: PRODUCT DESCRIPTION:NO. 5359 EP FOAM-A-COIL (AERO)

MANUFACTURER:
ENGINEER'S PRIDE
PO BOX 6845
ATLANTA, GA 30315
EMERGENCY (800) 535-5053
M-F 9-5 (800) 849-7958
PREPARED BY: RICK GLISSON
DATE PREPARED: 09/14/01

SECTION II:
HAZARDOUS INGREDIENTS: CAS #: %: TIV SARA III, #313
1) 2 - BUTOXYETHANOL. 111-76-2 7-8 25 PPM *
2) ISOPROPANE - ISOBUTANE N/A 5 NOT EST.
PROPELLANT N/A

SECTION III: PHYSICAL DATA
BOILING POINT (DEG. F.): 21.2
VAPOR PRESSURE (MM HG.): 2
VAPOR DENSITY (AIR=1): 2
SOLUBILITY (AIR=1): HEAVIER
SPECIFIC GRAVITY (WATER=1): COMPLETE
PERCENT VOLATILE BY VOLUME (4): 1.0
EVAPORATION RATE (ETHER =1): SLOWER THAN ETHER.
APPEARANCE AND ODOR: MATERIAL COMES OUT OF THE CAN AS A WHITE FOAM WITH A LEMON-MINT ODOR.
PH: 12.5

SECTION IV: FIRE AND EXPLOSION DATA
FLASH POINT (METHOD USED): 143 DEG. F. (2-BUTOXYETHANOL)
FLAMMABLE LIMITS: LEL: 1.1% AT 93 DEG. C. UEL: 12.7% AT 135 DEG. C.
EXTINGUISHING MEDIA: DRY CHEMICAL, FOAM, CARBON DIOXIDE, WATER
SPECIAL FIRE FIGHTING PROCEDURES: SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN PRESSURE-DEMAND OR OTHER POSITIVE PRESSURE MODE
UNUSUAL FIRE AND EXPLOSION HAZARDS : EXPOSURE TO TEMPERATURES OVER 130 DEG. F. MAY CAUSE CAN TO BURST.

TRANSPORTATION: DOT HAZARD CLASSIFICATION: ORM-D
MATERIAL SAFETY DATA SHEET NO. 5359 EP FOAM-A-COIL (AERO)

PAGE 2

SECTION V : HEALTH HAZARD DATA
THRESHOLD LIMIT VALUE: 25 PPM (2-BUTOXYETHANOL)
EFFECTS OF OVEREXPOSURE: EYES: CAUSES IRRITATION. SKIN: MAY BE HARMFUL IF ABSORBED THROUGH THE SKIN. INHALATION: MAY BE HARMFUL IF INHALED.
INGESTION: MAY BE HARMFUL IF SWALLOWED.
EMERGENCY & FIRST AID PROCEDURES: EYES: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES AND GET MEDICAL ATTENTION. SKIN: IMMEDIATELY FLUSH WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES WHILE REMOVING CONTAMINATED CLOTHING AND SHOES. GET MEDICAL ATTENTION. WASH CONTAMINATED CLOTHING BEFORE REUSE. INHALATION: REMOVE FROM EXPOSURE, TREAT SYMPTOMATICALLY, AND GET MEDICAL ATTENTION. INGESTION: IF CONSCIOUS INDUCE VOMITING IMMEDIATELY BY GIVING TWO GLASSES OF WATER AND STICKING FINGER DOWN THROAT. GET MEDICAL ATTENTION AS SOON AS POSSIBLE. NEVER GIVE ANYTHING BY MOUTH TO AN UNCONSCIOUS PERSON.
CARCINOGENICITY: NONE KNOWN. PRIMARY ROUTES OF EXPOSURE: SKIN, INHALATION

SECTION VI : REACTIVITY DATA
STABILITY: STABLE
CONDITIONS TO AVOID: EXPOSURE TO TEMPERATURES OVER 130 DEG. F. MAY CAUSE CAN TO BURST
INCOMPATIBILITY: STRONG OXIDIZERS
HAZARDOUS DECOMPOSITION PRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE

SECTION VII: SPILL OR LEAK PROCEDURES
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SMALL SPILL: FLUSH DOWN WITH PLENTY OF WATER. LARGE SPILL: SOAK UP WITH ABSORBENT MATERIAL.
WASTE DISPOSAL METHOD: SMALL SPILL: FLUSH DOWN WITH PLENTY OF WATER. LARGE SPILL: ABSORBENT MAY BE CARTED TO A LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

SECTION VIII: SPECIAL PROTECTION INFORMATION
RESPIRATORY PROTECTION (SPECIFY TYPE): NONE NORMALLY NEEDED.
VENTILATION (LOCAL, MECHANICAL, SPECIAL): NONE NORMALLY NEEDED.
PROTECTIVE GLOVES: RUBBER
EYE PROTECTION: CHEMICAL SPLASH PROOF GOGGLES.
OTHER PROTECTIVE EQUIPMENT: NONE

SECTION IX: SPECIAL PRECAUTIONS
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE:
ALWAYS STORE UNUSED PORTION IN ORIGINAL CONTAINER WITH CAP SECURE.
NEVER STORE IN UNLABELED OR IMPROPERLY LABELED CONTAINER.
STORE IN A COOL DRY PLACE.



OTHER PRECAUTIONS:
AS WITH ALL CHEMICALS, USE WITH DUE CARE ACCORDING TO LABEL
INSTRUCTIONS AND PRECAUTIONS.
KEEP OUT OF REACH OF CHILDREN. FOR COMMERCIAL/INDUSTRIAL USE ONLY.

WARNING: THIS PRODUCT CONTAINS A CHEMICAL THAT IS KNOWN TO THE STATE OF
CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.
ACETALDEHYDE, 1,4-DIOXANE, FORMALDEHYDE, ETHYLENE OXIDE.