

#/

64

SECTION VII ENVIRONMENTAL HAZARD - SPILL OUTLINE PROCEDURES

POTENTIAL AS A POLLUTANT

Gas - general hydrocarbon

Combustion products - CO and various aldehydes

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Extinguish all fires, eliminate sparking equipment, ventilate well

WASTE DISPOSAL METHOD

Allow spills to evaporate with adequate ventilation. Burn under controlled conditions using pressure regulator or control valve.

SECTION VIII

SPECIAL PROTECTION INFORMATION Not needed unless spill occurs.

RESPIRATORY PROTECTION (Specify type)

Chemical cartridge or airline

VENTILATION

LOCAL EXHAUST

Recommended

SPECIAL

Explosion proof

MECHANICAL (general)

OTHER

PROTECTIVE GLOVES (Type if required)

EYE PROTECTION

Chemical goggles

OTHER PROTECTIVE EQUIPMENT

SECTION IX

SHIPPING REGULATIONS FOR HAZARDOUS MATERIAL

A. IS THE ARTICLE SUBJECT TO SHIPPING REGULATION FOR HAZARDOUS MATERIAL UNDER EACH OF THE FOLLOWING MODES (1)
REFER TO INSTRUCTIONS MATERIAL SAFETY DATA SECTION IX.RAIL
TRUCK
YES ☒ NO ☐
☒ ☐BUS
AIR (2)
YES ☒ NO ☐
☒ ☐PARCEL POST
WATER CARRIER
YES ☒ NO ☐
☒ ☐UNITED PARCEL
YES ☒ NO ☐
☒ ☐

IDMR IMCO CLASS 2

UN #1075

IMDG CODE PAGE 2070

TYPE OR CLASS DESCRIBED IN THE REGULATIONS

Flammable Gas

PROPER SHIPPING NAME (TRUE CHEMICAL OR OTHER NAME AS LISTED IN THE REGULATIONS)

Liquefied Petroleum Gas (Propane)

PACKAGING REQUIREMENTS AND SPEC. IF APPLICABLE

DOT 39 NRC

SIZE OR QUANTITY IN PACK

16 oz.

MAXIMUM QUANTITY OR GROSS WEIGHT LIMITS FOR FOLLOWING MODES

RAIL none

BUS can not be used

TRUCK none

PARCEL POST 27.5 Kg.

WATER CARRIER none

UNITED PARCEL IATA Article #1023

AIR 300#

Packing note #200

Air freight only

MARKING REQUIREMENTS FOR OUTER CONTAINER

MODE
RAIL ☒
TRUCK ☒
WATER CARRIER ☒
AIR cargo only ☒
BUS ☒
PARCEL POST ☒
UNITED PARCEL ☒MARKING CONTENTS:
Liquefied petroleum gas. Inside containers comply with prescribed DOT regulations.
THIS END UP

LABEL REQUIRED IF NOT EXEMPT

MODE
RAIL ☒
TRUCK ☒
WATER CARRIER ☒
AIR cargo only ☒
BUS ☒
PARCEL POST ☒
UNITED PARCEL ☒

LABEL

FLAMMABLE GAS

C. SHIPPING PAPERS OR DOCUMENTS INFORMATION

CERTIFICATE REQUIRED
CHARGED PRESSURE 200 psi typ. 95°F
CUBIC INCH DISPLACEMENT OF PRESSURE VESSEL
SPECIAL STOWAGE REQUIREMENT OR INSTRUCTION FOR CARRIER
See Section VIYES ☒ NO ☐
73.7
☒ ☐OTHER INFORMATION Cannot be shipped by bus or passenger aircraft. Ship on passenger vessels as deck cargo only.
Ship inlet end up.PLACARDING REQUIREMENTS
FLAMMABLE GAS

SECTION X

SPECIAL PRECAUTION & CONCLUSION

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Handle per 49 CFR 172.101

BY

TITLE

DATE