

CUSTOMER: 327598
BATCH #: 1696453
PICK ZONE: RW02
PRODUCT NAME: TEL-X PLUS AEROSOL, MM

ORDER #: 1699965
DELIVERY ID: 12586950
PICK SEQUENCE #: 1250
BARCODE #: 12039398

Material Safety Data Sheet: TEL-X PLUS AEROSOL, MM

Supersedes Date 04/01/2011

Issuing Date 07/30/2014

1. PRODUCT AND COMPANY IDENTIFICATION

Product Name TEL-X PLUS AEROSOL, MM
Recommended use Lubricant
Information on Manufacturer
CERTIFIED LABS, DIV. OF NCH CORP.
BOX 152170
IRVING, TEXAS 75015

Product Code 12039398
Chemical nature Resins in solution
Emergency Telephone Number
CHEMTREC® 800-424-9300

2. HAZARDS IDENTIFICATION

Emergency Overview
DANGER
Extremely flammable
May be harmful if inhaled
May cause skin irritation
Causes eye irritation
May be harmful if swallowed

Color White	Physical State Liquid	Odor Rubbing alcohol
Potential Health Effects		
Principle Route of Exposure	Inhalation, Skin contact, Eye contact.	
Primary Routes of Entry	Inhalation	
Acute Effects		
Eyes	Causes eye irritation.	
Skin	May cause skin irritation.	
Inhalation	May cause irritation of respiratory tract. Inhalation may cause central nervous system effects. May cause central nervous system depression. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. May be fatal if inhaled in large quantities.	
Ingestion	Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.	
Chronic Toxicity	May cause polymer fume fever, a temporary flu-like illness accompanied by chills, fever, and a cough. This can last up to 24 hours in duration. Prolonged or repeated exposure increases the risk. Liver and kidney injuries may occur.	
Target Organ Effects	Eyes, Skin, Respiratory system, Central nervous system, Liver, Kidney.	
Aggravated Medical Conditions	Skin disorders, Respiratory disorders, Neurological disorders, Liver disorders, Kidney disorders.	
Potential Environmental Effects	See Section 12 for additional Ecological information.	

3. COMPOSITION / INFORMATION ON INGREDIENTS

Component	CAS-No
Isopropyl alcohol	67-63-0
Butane	106-97-8
Propane	74-98-6
Polytetrafluoroethylene	9002-84-0

4. FIRST AID MEASURES

General advice	Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist, or gas.
Eye Contact	Rinse thoroughly with plenty of water, also under the eyelids. Get medical attention if irritation develops and persists.
Skin Contact	Wash off immediately with plenty of water for at least 15 minutes. Remove contaminated clothing and shoes. Get medical attention if irritation develops and persists. Wash contaminated clothing before re-use.
Inhalation	If inhaled, remove to fresh air. Get medical attention if symptoms occur.
Ingestion	Drink 1 or 2 glasses of water. Do NOT induce vomiting. Get medical attention if symptoms occur. Never give anything by mouth to an unconscious person.
Notes to physician	Treat symptomatically.

404

5. FIRE-FIGHTING MEASURES

Flash Point 53 °F / 12 °C **Method** Seta closed cup

Autoignition Temperature No information available.

Flammability Limits in Air % Propellant. **Upper** 12.7 **Lower** 1.8

Suitable Extinguishing Media
Foam. Alcohol-resistant foam. Dry chemical. Water spray. Carbon dioxide (CO₂). Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable Extinguishing Media
None known.

Specific hazards arising from the chemical
Solvent vapors are heavier than air and may spread along floors. Vapors may ignite and explode. Flame extension: 30 inches / 75 cm and Burnback: 0 inch / 0 cm.

Protective Equipment and Precautions for Firefighters
As in any fire, wear self-contained breathing apparatus pressure -demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Aerosol Level (NFPA 30B) - 3

NFPA	Health 2	Flammability 4	Instability 0
HMIS	Health 2	Flammability 4	Instability 0

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions Use personal protective equipment. Ensure adequate ventilation. Take precautionary measures against static discharges. Remove all sources of ignition. Material can create slippery conditions.

Environmental Precautions Do not flush into surface water or sanitary sewer system.

Methods for Containment Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13)

Methods for Cleaning Up Use clean non-sparking tools to collect absorbed material. Pick up and transfer to properly labeled containers.

Neutralizing Agent Not applicable.

7. HANDLING AND STORAGE

Handling Keep away from open flames, hot surfaces and sources of ignition. Avoid contact with skin, eyes and clothing. Avoid breathing vapors, mist or gas.

Storage Keep away from heat and sources of ignition.

Storage Temperature	Minimum 35 °F / 2 °C	Maximum	120 °F / 49 °C
Storage Conditions	Indoor X	Outdoor	Heated Refrigerated

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines

Component	ACGIH TLV	OSHA PEL	NIOSH
Isopropyl alcohol	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m ³	2000 ppm STEL 500 ppm STEL 1225 mg/m ³ TWA: 400 ppm TWA: 980 mg/m ³
Butane	STEL: 1000 ppm	No data available	TWA: 800 ppm TWA: 1900 mg/m ³
Propane	TWA: 1000 ppm	TWA: 1000 ppm TWA: 1800 mg/m ³	2100 ppm TWA: 1000 ppm TWA: 1800 mg/m ³

Engineering Measures Ensure adequate ventilation, especially in confined areas. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction.

Personal Protective Equipment

- Eye/Face Protection** Safety glasses with side-shields.
- Skin Protection** For prolonged or repeated contact, use protective gloves with appropriate chemical resistance.
- Respiratory Protection** In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

General Hygiene Considerations Wear protective gloves/clothing. Ensure that eyewash stations and safety showers are close to the workstation location. Remove and wash contaminated clothing before re-use.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State	Liquid	Viscosity	Slight viscous
-----------------------	--------	------------------	----------------

Color	White	Odor	Rubbing alcohol
Appearance	Hazy	pH	Not applicable
Specific Gravity	0.69	Evaporation Rate	51.6 (BuAc = 1)
Percent Volatile (Volume)	99.7	VOC Content (%)	99.0
VOC Photoreactive (Y/N)	Yes	VOC Content (g/L)	682
Vapor Pressure	1301 mmHg @ 70°F	Vapor Density	1.9 (air = 1)
Solubility	Moderately soluble	Boiling Point/Range	180 °F / 82 °C

10. STABILITY AND REACTIVITY

Chemical Stability	Stable. Hazardous polymerization does not occur.
Conditions to Avoid	Keep away from open flames, hot surfaces, and sources of ignition
Incompatible Products	Strong oxidizing agents, Strong acids, Aluminium.
Hazardous Decomposition Products	Carbon oxides, Hydrogen fluoride, Fluorinated hydrocarbons.
Possibility of Hazardous Reactions	None under normal processing

11. TOXICOLOGICAL INFORMATION

Product Information No information available.

Component Information

Acute Toxicity

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation	Draize Test	Other
Isopropyl alcohol	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rabbit)	= 16000 ppm (Rat) 8 h	no data available	no data available
Butane	no data available	no data available	= 658 g/m ³ (Rat) 4 h	no data available	no data available
Propane	no data available	no data available	= 658 mg/L (Rat) 4 h	no data available	no data available

Chronic Toxicity

Component	Mutagenicity	Sensitization	Developmental Toxicity	Reproductive Toxicity	Target Organ Effects
Isopropyl alcohol	no data available	no data available	no data available	no data available	eyes, respiratory system, skin, liver, kidney, CNS
Butane	no data available	no data available	no data available	no data available	CNS, heart
Propane	no data available	no data available	no data available	no data available	CNS, heart

Carcinogenicity There are no known carcinogenic chemicals in this product.

Component	ACGIH	IARC	NTP	OSHA	Other
Polytetrafluoroethylene	not applicable	Group 3	not applicable	not applicable	not applicable

12. ECOLOGICAL INFORMATION

Product Information No information available.

Component Information

Component	Toxicity to Algae	Toxicity to Fish	Microtox	Water Flea	log Pow
Isopropyl alcohol	EC50 > 1000 mg/L Desmodesmus subspicatus 72 h EC50 > 1000 mg/L Desmodesmus subspicatus 96 h	LC50 = 11130 mg/L Pimephales promelas 96 h LC50 = 9640 mg/L Pimephales promelas 96 h LC50 > 1400000 µg/L Lepomis macrochirus 96 h	EC50 = 35390 mg/L 5 min	EC50 13299 mg/L Daphnia magna 48 h	0.05
Butane	no data available	no data available	no data available	no data available	2.89
Propane	no data available	no data available	no data available	no data available	2.3

Persistence and Degradability No information available.
Bioaccumulation No information available.
Mobility No information available.

13. DISPOSAL CONSIDERATIONS

Product Disposal Dispose of in accordance with local regulations.
Container Disposal Contents under pressure. Do not puncture. Empty containers should be taken for local recycling, recovery, or waste disposal. Empty remaining contents.

14. TRANSPORT INFORMATION

404

DOT
 Proper Shipping Name Consumer commodity
 Hazard Class ORM-D
 Description Consumer commodity ,ORM-D,

TDG
 Proper shipping name Aerosols
 Hazard Class 2.1
 UN-No UN1950
 Description AEROSOLS,2.1,UN1950 LTD. QTY.

ICAO
 UN-No UN1950
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 Shipping Description Aerosols,UN1950 LTD. QTY.

IATA
 UN-No UN1950
 Proper Shipping Name Aerosols, flammable
 Hazard Class 2.1
 ERG Code 10L
 Shipping Description UN1950,Aerosols, flammable,2.1 LTD. QTY.

IMDG/IMO
 Proper Shipping Name Aerosols
 Hazard Class 2.1
 UN-No UN1950
 EmS No. F-D, S-U
 Shipping Description UN1950, Aerosols,2.1 LIMITED QUANTITIES

15. REGULATORY INFORMATION

Inventories

TSCA Complies
 DSL Complies

U.S. Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Component	CAS-No	Weight %	SARA 313 - Threshold Values
Isopropyl alcohol	67-63-0	40-70	1.0

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Chronic Health Hazard	Fire Hazard	Sudden Release of Pressure Hazard	Reactive Hazard
Yes	Yes	Yes	Yes	No

CERCLA

Canada

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS Hazard Class

A Compressed gases B5 Flammable aerosol D2B Toxic materials



16. OTHER INFORMATION

Prepared By Rachael Mohochi
 Supersedes Date 04/01/2011
 Issuing Date 07/30/2014
 Reason for Revision No information available.
 Glossary No information available.
 List of References. No information available.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or

disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage or disposal of the product. The information provided on this document is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

404

