

MATERIAL SAFETY DATA SHEET: PENTRA-FOAM AEROSOL

Section I - General Information

(000000-000000- - 5581)

Date of Issue:
6/27/2008 12:00:00 AM

Supersedes:
6/27/2008 12:00:00 AM

Chemical Name & Synonyms:
N/A

Trade Name & Synonyms:
PENTRA-FOAM AEROSOL

Chemical Family:
AEROSOL PETROLEUM MIXTURE

Formula is a mixture: [x]

Manufacturer Name:
CERTIFIED LABS, DIV. OF NCH CORP.

Manufacturer Address:
BOX 152170
IRVING, TEXAS 75015

Prepared By:
M McDowell/Chemist

Product Code Number:
5581

Emergency Phone Number:
800-424-9300

Section II - Hazardous Ingredients

THE HAZARDS PRESENTED BELOW ARE THOSE OF THE INDIVIDUAL COMPONENTS

Chemical Name (Ingredients)	Hazard	TLV	PEL	STEL	CAS #
PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC	IRRITANT	5 MG/M3 \$* 5 MG/M3	\$2 10 MG/M3	\$1 64742-88-4	
PETROLEUM DISTILLATES, SOLVENT-DEWAXED HEAVY PARAFFINIC	IRRITANT	5 MG/M3 \$1 5 MG/M3	\$2 10 MG/M3	\$1 64742-65-0	
CHLORINATED PARAFFIN	IRRITANT	5 MG/M3 \$1 5 MG/M3	\$2 10 MG/M3	\$1 63449-39-8	
PROPANE	FLAM/ASPHY	1000 PPM#1	1000 PPM 2	N/E	74-98-6
N-BUTANE	FLAM/ASPHY	1000 PPM#1	N/E 2	N/E	106-97-6

\$ OIL MIST VALUES
ALIPHATIC HYDROCARBON GASES

Section III - Physical Data

Boiling Point (°F): 810°	Specific Gravity (H ₂ O=1): 0.828
Vapor Pressure (mm Hg): 1841.9	Color: LIGHT AMBER
Vapor Density (Air=1): 1.7	Odor: PETROLEUM
pH @ 100% : N/A	Clarity: HAZY
% Volatile by Volume: 65	Evaporation Rate (BuAc=1): 24.5
H ₂ O Solubility: NEGLIGIBLE	Viscosity: SLIGHT VISCOUS

Section IV - Fire and Explosion Hazard

Flash Point: 410°F
Flammable Limits: PRODUCT MIXTURE
LEL: 0.9%

Method Used: T.C.C.
UEL: 9.5%
Aerosol Level (NFPA 30B): 3

Extinguishing Media: _____

NFPA 704 Hazard Rating: _____

<input type="checkbox"/> Foam	<input type="checkbox"/> Alcohol Foam	<input type="checkbox"/> CO2
<input checked="" type="checkbox"/> Dry Chemical	<input checked="" type="checkbox"/> Water Spray	<input type="checkbox"/> Other

4-Extreme	Health: 1
3-High	Flammability: 4
2-Moderate	Instability: 0
1-Slight	Special:
0-Insignificant	

Special Fire Fighting Procedures:

FIREFIGHTERS SHOULD WEAR A SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE GEAR. COOL FIRE-EXPOSED CONTAINERS WITH WATER SPRAY TO PREVENT BURSTING.

Unusual Fire and Explosion Hazards:

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL TO DISTANT AND/OR LOW-LYING SOURCES OF IGNITION AND FLASHBACK. PRODUCT MAY PRODUCE A FLOATING FIRE HAZARD AS LIQUID FLOATS ON WATER. THE USE OF WATER SPRAY (FOG) WHILE EFFECTIVE, MAY CAUSE FROTHING AND FOAMING. NEVER USE A WATER JET AS THIS WILL JUST SPREAD THE FIRE. FLAME EXTENSION IS >18 INCHES, BURNBACK IS 0 INCHES.

Section V - Health and Hazard Data

Threshold Limit Value:

NOT ESTABLISHED FOR MIXTURE. SEE SECTION II.

Effects of Overexposure:**Acute: (Short Term Exposure)**

EYE CONTACT: MAY CAUSE IRRITATION SEEN AS STINGING, TEARING, AND REDNESS. SKIN CONTACT: MAY CAUSE IRRITATION SEEN AS ITCHING AND REDNESS. PROLONGED OR REPEATED CONTACT AS FROM CLOTHING WET WITH MATERIAL MAY CAUSE DRYING, DEFATTING, AND CRACKING OF THE SKIN. INJECTION UNDER THE SKIN, IN MUSCLE, OR INTO THE BLOOD STREAM CAN CAUSE IRRITATION, INFLAMMATION, SWELLING, FEVER, AND SYSTEMIC EFFECTS, AND MILD CENTRAL NERVOUS SYSTEM DEPRESSION. INJECTION OF PRESSURIZED HYDROCARBONS CAN CAUSE SEVERE, PERMANENT TISSUE DAMAGE. INITIAL SYMPTOMS MAY BE MINOR. INHALATION: PRODUCT VAPORS DISPLACE AIR AND CAN CAUSE ASPHYXIATION, ESPECIALLY IN CONFINED SPACES. AT LOWER CONCENTRATIONS, CAN CAUSE NAUSEA, VOMITING, COUGHING, AND PULMONARY IRRITATION. AT HIGH VAPOR CONCENTRATIONS, CAN CAUSE HEADACHE, DIZZINESS, WEAKNESS, DISORIENTATION, LACK OF COORDINATION, PERIPHERAL NUMBNESS, HEART IRREGULARITIES, UNCONSCIOUSNESS, COMA, AND DEATH. INGESTION: MAY CAUSE IRRITATION WITH POSSIBLE NAUSEA, VOMITING, AND DIARRHEA.

Chronic: (Long Term Exposure)

ON RARE OCCASIONS, PROLONGED AND REPEATED EXPOSURE TO OIL MIST POSES A RISK OF CHRONIC LUNG INFLAMMATION. THIS CONDITION IS USUALLY ASYMPTOMATIC AS A RESULT OF REPEATED SMALL ASPIRATIONS. SHORTNESS OF BREATH AND COUGHING ARE THE MOST COMMON SYMPTOMS. ASPIRATION MAY LEAD TO PULMONARY EDEMA AND HEMORRHAGE AND MAY BE FATAL. SIGNS OF LUNG INVOLVEMENT INCLUDE INCREASED RESPIRATION AND HEART RATES AS WELL AS A BLUISH DISCOLORATION OF THE SKIN. CHRONIC SKIN CONTACT MAY PROMOTE DERMATITIS AND OIL ACNE. IN RARER CASES, AN INCREASED SENSITIVITY TO SUNLIGHT (PHOTOSENSITIVITY) MAY OCCUR. MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE ARE PRE-EXISTING RESPIRATORY AND SKIN CONDITIONS SUCH AS ASTHMA, EMPHYSEMA, AND DERMATITIS. CARDIOVASCULAR SYSTEM. TARGET ORGANS: HEART, LIVER, AND CENTRAL NERVOUS SYSTEM. THE PRIMARY ROUTES OF EXPOSURE ARE SKIN AND EYE CONTACT.

Primary Routes of Entry

<input checked="" type="checkbox"/> Inhalation	<input type="checkbox"/> Ingestion	<input type="checkbox"/> Absorption
--	------------------------------------	-------------------------------------

Emergency First Aid Procedures:**Inhalation:**

REMOVE FROM THE AREA TO FRESH AIR. SEEK MEDICAL ATTENTION IF RESPIRATORY IRRITATION DEVELOPS OR IF BREATHING BECOMES DIFFICULT.

Eye Contact:

RINSE THE EYES WITH WATER. REMOVE ANY CONTACT LENSES AND CONTINUE FLUSHING WITH PLENTY OF WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

Skin Contact:

WASH AFFECTED AREAS WITH PLENTY OF SOAP AND WATER FOR SEVERAL MINUTES. SEEK MEDICAL ATTENTION IF IRRITATION DEVELOPS.

Ingestion:
GIVE 3 TO 4 GLASSES OF WATER, BUT DO NOT INDUCE VOMITING. IF VOMITING OCCURS, GIVE FLUIDS AGAIN. SEEK MEDICAL ATTENTION IF DISCOMFORT OCCURS.

Notes to Physician:
THERE IS NO SPECIFIC ANTIDOTE. TREAT THE PATIENT SYMPTOMATICALLY. IN THE EVENT OF INJECTION IN UNDERLYING TISSUE, IMMEDIATE TREATMENT SHOULD INCLUDE EXTENSIVE INCISION, DEBRIDEMENT AND SALINE IRRIGATION. INADEQUATE TREATMENT CAN RESULT IN ISCHEMIA AND GANGRENE. EARLY SYMPTOMS MAY BE MINIMAL.

Section VI - Toxicity Information

Product Contains Chemicals Listed as Carcinogen or Potential Carcinogen By: IARC NTP OSHA ACGIH Other

VOC CONTENT: 10% BY WEIGHT; 16% BY VOLUME; 83 G/L

PETROLEUM DISTILLATES, HYDROTREATED HEAVY PARAFFINIC (<3% DMSO EXTRACTABLE MATERIAL)

ORL-RAT LD50: > 2 G/KG 3.

SKN-RBT LD50: > 2 G/KG 3.

IHL-RAT LC50: > 5 MG/L 3.

EYE-RBT DRAIZE SCORE BETWEEN 6 AND 15, PRACTICALLY NON-IRRITATING 3.

SKN-RBT DRAIZE SCORE BETWEEN .5 AND 3, PRACTICALLY NON-IRRITATING 3.

PETROLEUM DISTILLATES, SOLVENT DEWAXED HEAVY PARAFFINIC (<3% DMSO EXTRACTABLE MATERIAL)

ORL-RAT LD50: >5 GM/KG 3.

IHL-RAT LC50: >5 MG/L DATA FOR SIMILAR COMPOUND 3.

SKN-RBT DRAIZED SCORE BETWEEN .5 AND 3, NON-IRRITATING 3.

EYE-RBT DRAIZED SCORE BETWEEN 6 AND 15, NON-IRRITATING 3.

CHLORINATED PARAFFIN

ORL-RAT LD50: >21500 UL/KG 4.

SKN-RBT LD50: >10 ML/KG 4.

SKN-RAT SDT: 100 MG/24H MILD 4.

EYE-RBT SDT: 100 MG MILD 4.

CHLORINATED PARAFFINS ARE A CLASS OF COMPOUNDS THAT ARE SIMILARLY MANUFACTURED BUT VARY IN MOLECULAR STRUCTURE BY CARBON CHAIN LENGTH AND DEGREE OF CHLORINATION. THIS PRODUCT HAS NOT BEEN SHOWN TO HAVE SIGNIFICANT ADVERSE HEALTH EFFECTS. 3.

PROPANE

IHL-LC50: >40% BY VOLUME 3.

N-BUTANE

IHL-RAT LC50: 658 GM/34H 4.

HUMAN VOLUNTEERS EXPOSED REPEATEDLY TO GASES OF SIMILAR HYDROCARON MIXTURES RANGING FROM 250 TO 1000 PPM EXHIBITED NO CARDIAC OR PULMONARY FUNCTION ABNORMALITIES. 3.

Section VII - Reactivity Data

Stability

Stable Unstable

Conditions to Avoid:

AVOID HEAT, HOT SURFACES, SPARKS, AND OPEN FLAMES.

Hazardous Polymerization

Will not occur May occur

Conditions to Avoid:

N/A

Incompatibility (Materials to Avoid):

STRONG OXIDIZING AGENTS SUCH AS CHLORINE BLEACH AND CONCENTRATED HYDROGEN PEROXIDE; REDUCING AGENTS SUCH AS SODIUM THIOSULFATE AND ALKALIS.

Hazardous Decomposition Products:

OXIDES OF CARBON, NITROGEN, AND SULFUR; HYDROGEN SULFIDE, HYDROGEN CHLORIDE GAS, ALDEHYDES, AND SMOKE.

Section VIII - Spill Or Leak Procedures

Steps to be Taken if Material is Released or Spilled:

DUE TO THE NATURE OF THE AEROSOL PACKAGING, A LARGE SPILL IS UNLIKELY. FOR A SMALL SPILL, VENTILATE THE AREA. USE CARE AS SPILLS MAY BE SLIPPERY. ABSORB WITH AN INERT MATERIAL AND TRANSFER ALL MATERIAL INTO A PROPERLY LABELED CONTAINER FOR DISPOSAL. WEAR APPROPRIATE PROTECTIVE CLOTHING. PREVENT PRODUCT FROM CONTAMINATING SOIL OR FROM ENTERING SEWAGE AND DRAINAGE SYSTEMS AND BODIES OF WATER.

Waste Disposal Method(s):

DISPOSE OF IN ACCORDANCE WITH ALL FEDERAL, STATE, AND LOCAL REGULATIONS. TYPICAL DISPOSAL IS TO WRAP THE EMPTY AEROSOL CONTAINER IN SEVERAL LAYERS OF NEWSPAPER AND DISPOSE OF IN THE TRASH. AEROSOL RECYCLING PROGRAMS ARE AVAILABLE IN MANY AREAS. DO NOT PUNCTURE OR INCINERATE THIS CONTAINER.

Neutralizing Agent:

N/A

Section IX - Special Protection Information

Required Ventilation:

LOCAL VENTILATION IS RECOMMENDED TO CONTROL EXPOSURE FROM OPERATIONS THAT CAN GENERATE MISTS OR VAPORS. LOCAL VENTILATION IS PREFERRED, BECAUSE IT PREVENTS DISPERSION INTO WORK AREAS BY CONTROLLING IT AT ITS SOURCE.

Respiratory Protection:

RESPIRATORS SHOULD BE SELECTED BY AND USED UNDER THE DIRECTION OF A TRAINED HEALTH AND SAFETY PROFESSIONAL FOLLOWING REQUIREMENTS FOUND IN OSHA'S RESPIRATOR STANDARD (29 CFR 1910.134) AND ANSIS STANDARD FOR RESPIRATORY PROTECTION (Z88.2-1992). FOR CONCENTRATIONS ABOVE THE TLV AND/OR PEL BUT LESS THAN 10 TIMES THESE LIMITS, A NIOSH APPROVED HALF-FACEPIECE RESPIRATOR EQUIPPED WITH APPROPRIATE CHEMICAL CARTRIDGES MAY BE USED. FOR CONCENTRATIONS GREATER THAN 10 TIMES THE TLV AND/OR PEL, CONSULT THE NIOSH RESPIRATOR DECISION LOGIC FOUND IN PUBLICATION NO. 87-116 OR ANSIS Z88.2-1992.

Glove Protection:

NEOPRENE OR NITRILE RUBBER GLOVES IF REPEATED OR PROLONGED SKIN CONTACT IS LIKELY. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR HAND PROTECTION, 29 CFR 1910.138.

Eye Protection:

SAFETY GLASSES WITH SIDE SHIELDS IF THE METHOD OF USE PRESENTS THE LIKELIHOOD OF EYE CONTACT. ENSURE COMPLIANCE WITH OSHA'S PERSONAL PROTECTIVE EQUIPMENT (PPE) STANDARD FOR EYE AND FACE PROTECTION, 29 CFR 1910.133.

Other Protection:

WEAR GENERAL DUTY WORK CLOTHING AND SHOES. REMOVE OIL SOAKED CLOTHING AND SHOES. WASH CLOTHING AND CLEAN SHOES BEFORE REUSE. A SAFETY SHOWER AND AN EYEWASH STATION SHOULD BE AVAILABLE.

Section X - Storage and Handling Information

Storage Temperature Max: 120°F Min: 10°F	Storage Conditions <input checked="" type="checkbox"/> Indoors <input checked="" type="checkbox"/> Outdoors <input type="checkbox"/> Heated <input type="checkbox"/> Refrigerated
---	---

Precautions to be Taken in Handling and Storing:

USE WITH CAUTION AROUND HEAT, SPARKS, PILOT LIGHTS, STATIC ELECTRICITY, AND OPEN FLAME.

Other Precautions:

KEEP OUT OF REACH OF CHILDREN. READ THE ENTIRE LABEL BEFORE USING THE PRODUCT. FOLLOW THE LABEL DIRECTIONS.

Section XI - Regulatory Information

Chemical Name	CAS Number	Upper % Limit
None.		

Those ingredients listed above are subject to the reporting requirements of 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR part 372.

Please call 1-800-527-9919 for additional information if you are a California customer. This MSDS is not intended for users in the state of California.

Section XII - References

1. THRESHOLD LIMIT VALUES FOR CHEMICAL SUBSTANCES AND PHYSICAL AGENTS AND BIOLOGICAL EXPOSURE INDICES, ACGIH, 2006.
2. OSHA PEL.
3. VENDOR'S MSDS.
4. REGISTRY OF TOXIC EFFECTS OF CHEMICAL SUBSTANCES, CCINFOWeb, 2006.

ALL THE COMPONENTS OF THIS PRODUCT ARE IN COMPLIANCE WITH THE TOXIC SUBSTANCES CONTROL ACT (TSCA) AND ARE EITHER LISTED ON THE TSCA INVENTORY OR OTHERWISE EXEMPTED FROM LISTING.

IRR:IRRITANT, FLAM/FLAMM:FLAMMABLE, COMB:COMBUSTIBLE, CORR:CORROSIVE CARC:CARCINOGENIC, TOX:TOXIC, N/A:NOT APPLICABLE, N/E:NOT ESTABLISHED, COC:CLEVELAND OPEN CUP, PMCC:PENSKY-MARTIN CLOSED CUP, TCC:TAGLIABUE CLOSED CUP, LEL:LOWER EXPLOSION LIMIT, UEL:UPPER EXPLOSION LIMIT, NFPA:NATIONAL FIRE PROTECTION ASSOCIATION, IARC:INTERNATIONAL AGENCY FOR THE RESEARCH ON CANCER, NTP:NATIONAL TOXICOLOGY PROGRAM, OSHA:OCCUPATIONAL SAFETY & HEALTH ADMINISTRATION, ACGIH:AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS, TLV:THRESHOLD LIMIT VALUE, PEL:PERMISSIBLE EXPOSURE LIMIT, STEL:SHORT-TERM EXPOSURE LIMIT, MLD:MILD, MOD:MODERATE, SEV:SEVERE, MUT: MUTAGENIC, ASPHYX:ASPHYXIAN, PNO5:PARTICLES (INSOLUBLE) NOT OTHERWISE SPECIFIED, PNOR:PARTICULATES NOT OTHERWISE REGULATED, SDT:STANDARD DRAIZE TEST, ORL:ORAL, IHL:INHALATION, HMN:HUMAN

THE INFORMATION CONTAINED HEREIN IS BASED ON DATA CONSIDERED ACCURATE IN LIGHT OF CURRENT FORMULATION. HOWEVER, NO WARRANTY IS EXPRESSED OR IMPLIED REGARDING THE ACCURACY OF THE DATA OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF.

CERTIFIED LABS, DIV. OF NCH CORP. assumes no responsibility for personal injury or property damage caused by the use, storage, or disposal of the product in a manner not recommended on the product label. Users assume all risks associated with such unrecommended use, storage, or disposal of the product.

©2007 NCH Corporation. All rights reserved.