

VI-HEALTH HAZARD DATA

OSHA PERMISSIBLE EXPOSURE LIMIT
523 ppm estimated

EFFECTS OF OVER EXPOSURE

INHALATION

Headache, dizziness, nausea, possible unconsciousness and death if vapor conc. exceeds TLV

SKIN CONTACT/ABSORPTION

Slight skin irritation

INGESTION

Nausea

EYES

Slight irritation

EMERGENCY AND FIRST AID PROCEDURES

EYES AND SKIN

Flush with plenty of water, if irritation persists, contact physician.

INHALATION

Remove to fresh air. Resuscitate if necessary and get medical aid.

INGESTION

Drink large volumes of water, induce vomiting, call physician.

VII-SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

Flush to sewer with water.

WASTE DISPOSAL METHOD

Aerosol cans, when vented to the atmosphere through normal use, pose no hazard.

VIII-SPECIAL PROTECTION INFORMATION

SPECIFIC PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY NONE

EYE

Safety glasses

SKIN

NONE

OTHER

NONE

VENTILATION REQUIREMENTS

adequate ventilation, normal air circulation

IX-SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

Do not puncture or incinerate container. Do not store at temperatures above 130°F.

OTHER PRECAUTIONS

Avoid food contamination. KEEP OUT OF REACH OF CHILDREN.