

MATERIAL SAFETY DATA SHEET
 COMPLIES WITH OSHA'S HAZARD COMMUNICATION STANDARD (29CFR 1910.1200)

135

SECTION I - PRODUCT IDENTIFICATION

PRODUCT NAME: **ARREST**
 PRODUCT NUMBER: 210
 PRODUCT TYPE: AEROSOL
 SUPPLIER'S NAME: **CHEMPACE CORPORATION**
 SUPPLIER'S ADDRESS: 45 BURLINGAME BLVD, TOLEDO, OH 43607
 D.O.T. HAZARD CLASS: ORM-D

Chemical Family: N/A
 Formula: Proprietary
 Date Prepared: 6/16/94
 Emergency Phone: 419/535-0101
 Information Phone: 419/535-0101

HMS RATING: (Based on Aerosol Concentrate): 0-Minimal; 1-Slight; 2-Moderate; 3-Serious; 4-Extreme

HEALTH 2
 FIRE 0
 REACTIVITY 1
 PERSONAL PROTECTION: B

SECTION II - INGREDIENTS

CHEMICAL NAME	CAS NO.	% WT	313/CHEM	PEL	SKIN	TWA-TLV	CARCINOGEN
1,1,1, Trichloroethane	71-55-6	60-80	YES	350 ppm	NO	350 ppm	NO
Butyl Cellosolve	111-78-2	01-05	NO	25 ppm	NO	25 ppm	NO
Mineral Oil	64742-65-0	10-20	NO	N/D	NO	N/D	NO
Carbon Dioxide Propellant	124-38-9	01-05	NO	10000 ppm	NO	10000 ppm	NO

SECTION III - PHYSICAL DATA

DATA BELOW BASED ON AEROSOL CONCENTRATE ONLY:
 Boiling Point: N.D.
 Vapor Density (Air=1): >1
 Solubility in Water: Slight.
 pH: N/A
 Specific Gravity (H₂O = 1) @ 75°F: 1.186

DATA BELOW BASED ON TOTAL CONTENTS:
 Vapor Pressure of Can (psig @ 70°F): 90
 Appearance/Odor : Clear Yellow Liquid, Mild Sweet Odor

SECTION IV - FIRE AND EXPLOSION DATA

Flash Point (OF CONCENTRATE ONLY): None to Boiling (200°F)
 Flammability as per USA Flame Projection Test: Non-Flammable Spray
 Extinguishing Media: Foam, CO₂, Dry Media

Special Fire Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.

Unusual Fire and Explosion Hazards: Exposure to temperatures above 120°F may cause bursting.

SECTION V - REACTIVITY DATA

Stability: Stable
 Hazardous Polymerization: Will Not Occur
 Compatibility: Avoid contact with strong oxidizing agents, aluminum and reactive metals.
 Hazardous Decomposition Products: Hydrogen Chloride, Phosgene.

SECTION VI - STORAGE AND HANDLING

KEEP OUT OF THE REACH OF CHILDREN
 For Industrial & Institutional Use Only.
 Store in a cool, dry area away from heat or open flame.
 Do not store at temperatures above 120°F.
 NFPA Code 30B Rating: Level 1 Aerosol

SECTION VII - HEALTH AND FIRST AID

PRIMARY ROUTES OF ENTRY & EFFECTS OF OVER EXPOSURE

EYES: May cause slight irritation but does not injure eye tissue.

SKIN: Frequent or prolonged contact may cause irritation

INHALATION: Inhalation of mist can cause irritation of nasal and respiratory passages. Abusive or excessive inhalation may cause irritation to the upper respiratory tract, dizziness, nausea, and other central nervous system effects

INGESTION: Can cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs can cause chemical pneumonitis.

FIRST AID PROCEDURES

EYES: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately.

SKIN: Wash with soap and water. If irritation persists seek medical attention.

INHALATION: Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration.

INGESTION: Do not induce vomiting. Seek medical attention immediately.

SECTION VIII - SPECIAL PROTECTION DATA

RESPIRATORY PROTECTION: None needed for proper use in accordance with label directions.

VENTILATION: Provide local exhaust to keep TLV of Section II ingredients below acceptable limits.

PROTECTIVE GLOVES: None needed for proper use in accordance with label directions. Use chemical resistant gloves if hand contact will be made.

EYE PROTECTION: None needed unless it is anticipated that a splash or sprayback will occur, then wear safety glasses.

SECTION IX - SPILL OR LEAK PRECAUTIONS

STEPS TO BE TAKEN IN CASE OF SPILL OR LEAK:

Allow propellant to evaporate.
 Maintain local exhaust and adequate ventilation.
 No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

WASTE DISPOSAL METHOD:

Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

NA=NOT APPLICABLE NE=NOT ESTABLISHED N/D=NOT DETERMINED <=LESS THAN >=MORE THAN

NOTICE: The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all-inclusive or fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.

135